

Notable Public Keys

STEVEN BALTAKATEI SANDOVAL

Email: baltakatei@gmail.com

Web: <https://reboil.com>

Front Matter

This book is copyright ©2021 by Steven Baltakatei Sandoval. This book is licensed under Creative Commons Attribution-ShareAlike 4.0 International License (CC BY-SA 4.0):

<https://creativecommons.org/licenses/by-sa/4.0/>

The book is available as source code in a `git` repository available at:

<https://reboil.com/gitweb/BK-2021-09.git>

This book was typeset using $\text{\TeX}_{\text{MACS}}$ version 2.1.1.

Fonts used include **Linux Libertine**.

This book was rendered on 2022-01-14T01:09:17+0000.

Table of contents

Front Matter	3
1 Trust through Stories	7
2 List of Public Keys	9
2.1 BITCOIN CORE	10
2.1.1 Background	10
2.1.2 History	10
2.1.3 Public Key Details	10
2.1.3.1 Binary Signing Key (v0.11.0–) (90C8 019E 36C2 E964)	10
2.1.3.2 Binary Signing Key (v0.9.3–v0.10.2) (7481 0B01 2346 C9A6)	11
2.1.3.3 Binary Signing Key (v0.8.6–v0.9.2.1) (29D9 EE6B 1FC7 30C1)	11
2.1.3.4 SATOSHI NAKAMOTO (18C0 9E86 5EC9 48A1)	11
2.2 CRYPTOMATOR	12
2.2.1 Background	12
2.2.2 History	12
2.2.3 Public Key Details	12
2.2.3.1 Binary signing key (–v1.5.7) (509C 9D63 34C8 0F11)	12
2.2.3.2 Binary signing key (v1.5.8–) (615D 449F E6E6 A235)	13
2.3 DEBIAN	14
2.3.1 Background	14
2.3.2 History	14
2.3.3 Public Key Details	14
2.3.3.1 Installation Image Signature Keys	14
2.3.3.2 Verbose key details	15
Key 1999-01-30 (7C3B 7970 88C7 C1F7)	15
Key 2000-09-16 (72FD C205 F6A3 2A8E)	15
Key 2004-06-20 (F82E 5CC0 4B2B 2B9E)	16
Key 2009-05-21 (39BE 2D72 5CEE 3195)	16
Key 2009-10-03 (9880 21A9 64E6 EA7D)	16
Key 2011-01-05 (DA87 E80D 6294 BE9B)	16
Key 2011-03-09 (6F95 B499 6CA7 B5A6)	16
Key 2013-05-06 (510A D6B9 AD11 CF6A)	16
Key 2014-01-03 (1239 00F2 A9B2 6DF5)	17
Key 2014-04-15 (4246 8F40 09EA 8AC3)	17
2.4 GITHUB	18
2.4.1 Background	18
2.4.2 History	18
2.4.3 Public Key Details	18
2.4.3.1 Web-flow commit signing (4AEE 18F8 3AFD EB23)	18
2.5 RASPIBLITZ	19
2.5.1 Background	19
2.5.2 History	19
2.5.3 Public Key Details	19
2.5.3.1 CHRISTIAN “ROOTZOL” ROTZOLL (1C73 060C 7C17 6461)	19
2.6 SATOSHI LABS	20
2.6.1 Background	20

2.6.2 History	20
2.6.3 Public Key Details	20
2.6.3.1 PAVOL RUSNÁK (91F3 B339 B9A0 2A3D)	20
2.6.3.2 2020 Signing Key (26A3 A566 62F0 E7E2)	20
2.6.3.3 2021 Signing Key (E21B 6950 A2EC B65C)	21
Appendix A How Public Key Cryptography Works	23
Appendix B How to use GnuPG	25
B.1 Definitions	25
B.2 Useful Commands	25
B.2.1 Obtaining keys	25
B.2.1.1 Import a public key	25
B.2.1.2 Download from a keyserver	25
B.2.2 Analyzing keys	26
B.2.2.1 View public key fingerprint	26
B.2.3 Sending keys	26
B.2.3.1 Export public key	26
B.2.4 Creating keys	26
B.2.4.1 Using default settings	26
B.2.4.2 With subkeys	26
Bibliography	27
Index	29

Chapter 1

Trust through Stories

This book contains stories about where certain public keys came from and a little about the people who use them.

Some people use public key cryptography to digitally sign their works. They do this so others can prove where copies of such works came from. Usually, digital tools automatically verify these digital signatures so people don't have to manually. However, in order to verify such tools, at some point a person must verify at least one digital signature for themselves.

Chapter 2

List of Public Keys

Each section in this chapter contains a story about a person or organization that uses a public-private key pair. Each story consists of some brief background information, a history of notable events, and public key information. Key fingerprints are included. Links to public keys are made available where possible.

2.1 BITCOIN CORE

2.1.1 Background

BITCOIN CORE is the “reference implementation” of the BITCOIN protocol. It is maintained by a group of people who have become known as the BITCOIN CORE developers.

Early in the blockchain’s history, the software that verified transactions against balances of previous transactions was a WINDOWS executable known as BITCOIN. The initial release of this software was by an entity that called themselves SATOSHI NAKAMOTO. Satoshi later gave up the code maintainer role of the project. The person who subsequently gained control was a person named GAVIN ANDRESEN. The software was rebranded from BITCOIN to BITCOIN CORE at version 0.9.0.^{2.1.1} A developer named WLADIMIR J. VAN DER LAAN became owner of the signing keys of the reference implementation starting at version 0.9.3. VAN DER LAAN originally used a personal key (7481 0B01 2346 C9A6) to sign binaries but later created a dedicated key (90C8 019E 36C2 E964) to sign binaries.

There exist various dubious theories regarding PGP key use by SATOSHI NAKAMOTO.^{2.1.2} The most likely candidate (18C0 9E86 5EC9 48A1) is one signed by BITCOIN CORE developers PETER TODD (7FAB 1142 67E4 FA04) and WLADIMIR J. VAN DER LAAN (7481 0B01 2346 C9A6).

2.1.2 History

2011-08-24. Creation date of VAN DER LAAN’s personal signing key 7481 0B01 2346 C9A6.

2011-12-15. Creation date of Andresen’s dedicated code signing key 29D9 EE6B 1FC7 30C1.

2013-03-23. Earliest snapshot of the <https://bitcoin.org> website on the INTERNET ARCHIVE.^{2.1.3} It is a redirect to <https://bitcoin.org/en>.

2013-04-11. Earliest snapshot of the <https://bitcoincore.org> website on the INTERNET ARCHIVE.^{2.1.4}

2013-07-27. Earliest snapshot of main GITHUB repository at <https://github.com/bitcoin/bitcoin> on the INTERNET ARCHIVE.^{2.1.5}

2014-03-19. The reference client rebranded from BITCOIN to BITCOIN CORE.

2014-04-08. Gavin Andresen steps down as lead developer. Hands over role to WLADIMIR J. VAN DER LAAN.^{2.1.6} Andresen maintains commit privileges to the GITHUB repository.

2015-06-24. Creation date of VAN DER LAAN’s dedicated code signing key 90C8 019E 36C2 E964.

2016-05-02. Gavin Andresen’s commit privileges were revoked by other BITCOIN CORE developers after Andresen published a blog post claiming Craig Wright was Satoshi Nakamoto.^{2.1.7}

2.1.3 Public Key Details

2.1.3.1 Binary Signing Key (v0.11.0–) (90C8 019E 36C2 E964)

This key^{2.1.8}, owned by WLADIMIR J. VAN DER LAAN, has been used to sign BITCOIN CORE releases since version 0.11.0.

```
pub  rsa4096/0x90C8019E36C2E964 2015-06-24 [SC] [expires: 2022-02-10]
     Key fingerprint = 01EA 5486 DE18 A882 D4C2 6845 90C8 019E 36C2 E964
uid  [ unknown] Wladimir J. van der Laan (Bitcoin Core ...) <laanwj@gmail.com>
```

2.1.1. See <https://bitcoin.org/en/release/v0.9.0#rebranding-to-bitcoin-core>.

2.1.2. See <https://www.vice.com/en/article/jpgq3y/satoshis-pgp-keys-are-probably-backdated-and-point-to-a-hoax>.

2.1.3. See <https://web.archive.org/web/20130323195546/http://bitcoin.org/en>.

2.1.4. See <https://web.archive.org/web/20130411033932/http://bitcoincore.org/>.

2.1.5. See <https://web.archive.org/web/20130727135658/https://github.com/bitcoin/bitcoin>.

2.1.6. See <https://www.coindesk.com/gavin-andresen-steps-bitcoins-lead-developer>.

2.1.7. See <https://twitter.com/peterktodd/status/727078284345917441>, <https://laanwj.github.io/2016/05/06/hostility-scams-and-moving-forward.html>, <https://www.bbc.com/news/technology-36202904>, and <https://www.theguardian.com/technology/2016/may/06/bitcoin-project-blocks-out-gavin-andresen-over-satoshi-nakamoto-claims>.

2.1.8. See https://reboil.com/res/2021/txt/20210719_90C8019E36C2E964..bitcoin_vanderlaan.asc

2.1.3.2 Binary Signing Key (v0.9.3–v0.10.2) (7481 0B01 2346 C9A6)

WLADIMIR VAN DER LAAN used his personal key^{2.1.9} to sign BITCOIN versions v0.9.3–v0.10.2.

```
pub  rsa2048/0x74810B012346C9A6 2011-08-24 [SC] [expires: 2022-02-10]
      Key fingerprint = 71A3 B167 3540 5025 D447 E8F2 7481 0B01 2346 C9A6
uid  [ unknown] Wladimir J. van der Laan <laanwj@visucore.com>
uid  [ unknown] Wladimir J. van der Laan <laanwj@gmail.com>
uid  [ unknown] Wladimir J. van der Laan <laanwj@protonmail.com>
sub  rsa2048/0x69B4C4CDC628F8F9 2017-05-17 [A] [expires: 2022-02-10]
sub  rsa2048/0xF69705ED890DE427 2011-08-24 [E]
sub  rsa2048/0x1E4AED62986CD25D 2017-05-17 [S] [expires: 2022-02-10]
```

2.1.3.3 Binary Signing Key (v0.8.6–v0.9.2.1) (29D9 EE6B 1FC7 30C1)

Gavin Andresen used this dedicated code-signing key^{2.1.10} to sign BITCOIN versions v0.8.6–v0.9.2.1. As of 2021-07-19, these versions and their signatures are available at <https://bitcoincore.org/bin/insecure/>.

```
pub  rsa4096/0x29D9EE6B1FC730C1 2011-12-15 [SC]
      Key fingerprint = 2664 6D99 CBAE C9B8 1982 EF60 29D9 EE6B 1FC7 30C1
uid  [ unknown] Gavin Andresen (CODE SIGNING KEY) <gavinandresen@gmail.com>
sub  rsa4096/0x1B7BFB457BF6E212 2013-11-01 [S]
sub  rsa4096/0x36E924A98E30B3ED 2011-12-15 [E]
```

2.1.3.4 SATOSHI NAKAMOTO (18C0 9E86 5EC9 48A1)

The dsa1024 algorithm this key^{2.1.11} uses is considered weak by the the NIST standard SP800-57 Part 1 Revision 5: *Recommendation for Key management*.^{2.1.12} The key offers only 80 bits of security against the possibility of impersonation via a brute force attack. Nevertheless, this key has a signature of BITCOIN CORE developer PETER TODD (7FAB 1142 67E4 FA04) dated 2013-10-12. Todd also committed the full fingerprint in a BITCOIN FOUNDATION document on 2013-04-26^{2.1.13}. This key also has a signature of BITCOIN CORE maintainer VLADIMIR J. VAN DER LAAN's personal key (7481 0B01 2346 C9A6) dated 2013-05-10, albeit revoked on 2016-05-02.

```
pub  dsa1024/0x18C09E865EC948A1 2008-10-30 [SC]
      Key fingerprint = DE4E FCA3 E1AB 9E41 CE96 CECB 18C0 9E86 5EC9 48A1
uid  [ unknown] Satoshi Nakamoto <satoshin@gmx.com>
sig 3  0x18C09E865EC948A1 2008-10-30 Satoshi Nakamoto <satoshin@gmx.com>
sig   0x74810B012346C9A6 2013-05-10 Wladimir J. van der Laan <laanwj@visucore.com>
sig 1  0x7FAB114267E4FA04 2013-10-12 Peter Todd <pete@petertodd.org>
rev   0x74810B012346C9A6 2016-05-02 Wladimir J. van der Laan <laanwj@visucore.com>
      reason for revocation: User ID is no longer valid
sub  elg2048/0xCF1857E6D6AAA69F 2008-10-30 [E]
sig   0x18C09E865EC948A1 2008-10-30 Satoshi Nakamoto <satoshin@gmx.com>
```

2.1.9. See https://reboil.com/res/2021/txt/20210719_74810B012346C9A6..bitcoin_vanderlaan.asc

2.1.10. See https://reboil.com/res/2021/txt/20210719_29D9EE6B1FC730C1..bitcoin_andresen.asc

2.1.11. See https://reboil.com/res/2021/txt/20210719_18C09E865EC948A1..bitcoin_nakamoto.asc

2.1.12. See <https://doi.org/10.6028/NIST.SP.800-57pt1r5>, table 2, page 54. dsa1024 keys have only offer 80 bits of security against brute force attacks.

2.1.13. See <https://github.com/pmlaw/The-Bitcoin-Foundation-Legal-Repo/commit/fb70771a9927e04ebe5ae33c46ba6589a9703e40>.

2.2 CRYPTOMATOR

2.2.1 Background

CRYPTOMATOR is a cross-platform file storage privacy application. It permits storing files on a third-party file storage services (e.g. DROPBOX) in encrypted form and accessible to the user as a virtual mountable drive. In other words, CRYPTOMATOR acts as an encryption layer between a user and a file storage service. Compiled binary releases are available for WINDOWS, MACOS, LINUX, ANDROID, and IOS^{2.2.1}.

As of 2021-12-22, the latest version of CRYPTOMATOR is version 1.6.5 (*Hotfix*) available on GITHUB^{2.2.2}. Judging from commit signatures of the GITHUB repository^{2.2.3}, the main developers appear to be SEBASTIAN STENZEL (667B 866E A824 0A09) ARMIN SCHRENK (748E 55D5 1F5B 3FBC), and TOBIAS HAGEMANN (69CE FAD5 1959 8989).

2.2.2 History

2015-01-01. First snapshot of <https://cryptomator.org> captured on the INTERNET ARCHIVE^{2.2.4}. Signature of latest version of CRYPTOMATOR (1.4.11) uses PGP key 509C 9D63 34C8 0F11^{2.2.5}.

2018-06-17. Binary signing PGP key 509C 9D63 34C8 0F11 published as GITHUB gist^{2.2.6}. Key used to sign CRYPTOMATOR versions prior to 1.5.8.

2020-09-01. Binary signing PGP key 615D 449F E6E6 A235 published as GITHUB gist^{2.2.7}. Key used to sign CRYPTOMATOR version 1.5.8 onward (as of 2021-12-22).

2020-09-02. Old binary signing PGP key 615D 449F E6E6 A235 signed by new PGP key 509C 9D63 34C8 0F11^{2.2.8}. Notice of revocation of old key and signing of new key by old key posted in GITHUB issue thread^{2.2.9}.

2.2.3 Public Key Details

2.2.3.1 Binary signing key (-v1.5.7) (509C 9D63 34C8 0F11)

PGP key used to sign compiled binary releases of CRYPTOMATOR prior to version 1.5.8.

```
pub  rsa4096/0x509C9D6334C80F11 2016-06-24 [SC] [expires: 2021-12-31]
    Key fingerprint = 5054 3A3D A4B1 DB81 DA3E 79CB 509C 9D63 34C8 0F11
uid  [ unknown] Cryptobot (Release Manager) <releases@cryptomator.org>
```

2.2.1. See <https://cryptomator.org/downloads/> .

2.2.2. See <https://github.com/cryptomator/cryptomator/releases/tag/1.6.5> .

2.2.3. See <https://github.com/cryptomator/cryptomator> .

2.2.4. See <https://web.archive.org/web/20150101033915/http://cryptomator.org/> .

2.2.5. Signature file at: https://web.archive.org/web/20210502041159/https://dl.bintray.com/cryptomator/cryptomator/1.4.11/cryptomator-1.4.11-x86_64.AppImage.asc . Signed file at: https://web.archive.org/web/20210502115653/https://dl.bintray.com/cryptomator/cryptomator/1.4.11/cryptomator-1.4.11-x86_64.AppImage .

2.2.6. See <https://gist.github.com/cryptobot/8ccf8fd686d0c2d8381b69126bb3f2f8> / 9fdeef62bddf9edf7b73f61f42423f1f123d3218 .

2.2.7. See <https://gist.github.com/cryptobot/211111cf092037490275f39d408f461a> / 1a8e133a1d7e6ae4eb2bcc0830e4567393e5162a .

2.2.8. See <https://gist.github.com/cryptobot/211111cf092037490275f39d408f461a> / d416c6f0d35506116436cbe2f872baa217f3f72a . Verify with `$ gpg --import` and `$ gpg --list-signatures` to show the signature (highlighted):

```
pub  rsa4096/0x615D449FE6E6A235 2020-08-18 [SC] [expires: 2031-01-01]
    Key fingerprint = 5811 7AFA 1F85 B3EE C154 677D 615D 449F E6E6 A235
uid  [ unknown] Cryptobot <releases@cryptomator.org>
sig  3 0x615D449FE6E6A235 2020-08-18 Cryptobot <releases@cryptomator.org>
sig  0x667B866EA8240A09 2020-08-18 [User ID not found]
sig  0x509C9D6334C80F11 2020-09-02 Cryptobot (Release Manager) <releases@cryptomator.org>
```

2.2.9. See <https://github.com/cryptomator/cryptomator.github.io/issues/25#issuecomment-685308263> .

2.2.3.2 Binary signing key (v1.5.8-) (615D 449F E6E6 A235)

PGP key used to sign compiled binary releases of CRYPTOMATOR after version *1.5.8* (as of 2021-12-22).

```
pub  rsa4096/0x615D449FE6E6A235 2020-08-18 [SC] [expires: 2031-01-01]
     Key fingerprint = 5811 7AFA 1F85 B3EE C154 677D 615D 449F E6E6 A235
uid  [ unknown] Cryptobot <releases@cryptomator.org>
```

2.3 DEBIAN

2.3.1 Background

DEBIAN is a free operating system from which many GNU/LINUX systems are derived. Such derived systems include UBUNTU, TAILS, KALI LINUX, and others.

DEBIAN is maintained by an association of developers who use GNUPG keys to sign announcements of software they contribute in order to protect against forgeries. A git repository containing GNUPG keyrings of DEBIAN keys is available at <https://salsa.debian.org/debian-keyring/keyring> or by installation of the `debian-keyring` package^{2.3.1} within a DEBIAN system.

The DEBIAN PROJECT was founded in 1993 by IAN ASHLEY MURDOCK. Various individuals have led the project since.^{2.3.2} As of 2021-09-25, the latest release of the operating system is called “DEBIAN 11 (BULLSEYE)”.

2.3.2 History

1993-08-16. The DEBIAN PROJECT officially founded by IAN ASHLEY MURDOCK.

1999-01-30. Creation date of the Debian CD signing key `7C3B 7970 88C7 C1F7`.

2000-09-16. Creation date of SANTIAGO GARCIA MANTINAN's key `72FD C205 F6A3 2A8E`.

2004-06-20. Creation date of DANIEL BAUMANN's key `F82E 5CC0 4B2B 2B9E`.

2009-10-03. Creation date of the Debian CD signing key `9880 21A9 64E6 EA7D`.

2011-01-05. Creation date of the Debian CD signing key `DA87 E80D 6294 BE9B`.

2014-04-15. Creation date of the Debian Testing CDs Automatic Signing Key `4246 8F40 09EA 8AC3`.

2.3.3 Public Key Details

2.3.3.1 Installation Image Signature Keys

The DEBIAN website makes available images of the operating system that can be installed onto and executed from removable media such as Compact Discs (CD), Digital Versatile Disc (DVD), and Universal Serial Bus (USB) storage devices. A set of GNUPG public key fingerprints have been listed on the `debian.org` website at <https://debian.org/CD/verify>. Table 2.3.1 summarizes the creation dates, long IDs, and availabilities of these keys. Full fingerprints and other information may be found in section 2.3.3.2.

2.3.1. See <https://tracker.debian.org/pkg/debian-keyring>

2.3.2. For a list of DEBIAN Project Leaders, see <https://www.debian.org/doc/manuals/project-history/leaders>.

Date	Long ID	Description	Available	Link
1999-01-30	7C3B 7970 88C7 C1F7	Debian CD signing key	2011–2015	2.3.3 2.3.4
2000-09-16	72FD C205 F6A3 2A8E	Santiago Garcia Mantinan	2011–2015	2.3.3 2.3.5
2004-06-20	F82E 5CC0 4B2B 2B9E	Daniel Baumann	2011–2015	2.3.3
2009-05-21	39BE 2D72 5CEE 3195	Daniel Baumann	2011–2015	2.3.3
2009-10-03	9880 21A9 64E6 EA7D	Debian CD signing key	2011–2021	2.3.3
2011-01-05	DA87 E80D 6294 BE9B	Debian CD signing key	2011–2021	2.3.3 2.3.4
2011-03-09	6F95 B499 6CA7 B5A6	Debian Live Signing Key	2012–2015	2.3.6
2013-05-06	510A D6B9 AD11 CF6A	Debian Live Signing Key	2013–2015	2.3.7
2014-01-03	1239 00F2 A9B2 6DF5	Live Systems Project	2014–2015	2.3.8
2014-04-15	4246 8F40 09EA 8AC3	Debian Testing CDs Automatic Signing Key	2014–2022	2.3.9

Table 2.3.1. A list of keys used to sign DEBIAN installation images. Keys identified from INTERNET ARCHIVE snapshots of <https://debian.org/CD/verify>.

2.3.3. See <https://web.archive.org/web/20110413065857/http://www.debian.org/CD/verify>.

2.3.6. See <https://web.archive.org/web/20120815030316/http://www.debian.org:80/CD/verify>.

2.3.7. See <https://web.archive.org/web/20130813130619/http://www.debian.org/CD/verify>.

2.3.8. See <https://web.archive.org/web/20140410065231/http://www.debian.org/CD/verify>.

2.3.9. See <https://web.archive.org/web/20140528012106/https://www.debian.org/CD/verify>.

2.3.4. Public key available at <https://web.archive.org/web/20210928205206/https://www.einval.com/~steve/pgp/>

2.3.5. Public key available at https://web.archive.org/web/20210928220426/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E..debian_manty.asc.

2.3.3.2 Verbose key details

Key 1999-01-30 (7C3B 7970 88C7 C1F7)

A 1024-bit DSA key that is the earliest dated key for signing Debian CDs mentioned at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE^{2.3.10}. Mention of this key was removed from that page by the end of 2015. A copy of this key can be found at the personal website of STEVE MCINTYRE, a debian developer.^{2.3.11}

```
pub dsa1024/0x7C3B797088C7C1F7 1999-01-30 [SCA] [revoked: 2017-01-11]
    Key fingerprint = AC65 6D79 E362 32CF 77BB B0E8 7C3B 7970 88C7 C1F7
uid [revoked] Steve McIntyre <steve@einval.com>
uid [revoked] Steve McIntyre <stevem@chiark.greenend.org.uk>
uid [revoked] Steve McIntyre <93sam@debian.org>
uid [revoked] Debian CD signing key <debian-cd@lists.debian.org>
```

Key 2000-09-16 (72FD C205 F6A3 2A8E)

A 1024-bit DSA key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE. Mention of this key was removed from that page by the end of 2015. A copy of this key was archived from the `pgp.mit.edu` keyserver.^{2.3.12} This 1024-bit DSA key was deprecated in favor of a 4096-bit RSA key with fingerprint B868 8CA3 D876 D5A3 in a signed blog post at `blog.manty.net`.^{2.3.13}

```
pub dsa1024/0x72FDC205F6A32A8E 2000-09-16 [SCA]
    Key fingerprint = 3F0A 12FC 0B55 A917 D791 82D3 72FD C205 F6A3 2A8E
uid [unknown] Santiago Garcia Mantinan (manty) <manty@debian.org>
uid [unknown] Santiago Garcia Mantinan (manty) <sgm@manty.net>
uid [unknown] Santiago Garcia Mantinan (manty) <manty@gpul.org>
sub elg1024/0x8F802C268D0EB704 2000-09-16 [E]
    Key fingerprint = 0481 1B16 A1BC E82B E985 26B7 8F80 2C26 8D0E B704
```

2.3.10. See <https://web.archive.org/web/20110413065857/http://www.debian.org/CD/verify>.

2.3.11. Key 7C3B 7970 88C7 C1F7 is available at <https://web.archive.org/web/20210928205229/https://www.einval.com/~steve/pgp/7C3B797088C7C1F7.asc>.

2.3.12. Key 72FD C205 F6A3 2A8E is available at https://web.archive.org/web/20210928220426/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E..debian_manty.asc.

2.3.13. Key transition statement available at <https://web.archive.org/web/20150614033612/http://blog.manty.net/2014/12/transitioning-from-0xf6a32a8e-to.html>. To verify, use `gpg --import` command on text copied from between the `<listing>` tags. A copy of this text is also archived at https://web.archive.org/web/20210928222521/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E_to_B8688CA3D876D5A3_pgp_transition_statement.txt.

Key 2004-06-20 (F82E 5CC0 4B2B 2B9E)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE. Mention of this key was removed from that page by the end of 2015.

```
pub  dsa1024/0xF82E5CC04B2B2B9E 2004-06-20 [SC] [expired: 2015-01-01]
     Key fingerprint = 709F 54E4 ECF3 1956 2332 6AE3 F82E 5CC0 4B2B 2B9E
uid  [ expired] Daniel Baumann <mail@daniel-baumann.ch>
```

Key 2009-05-21 (39BE 2D72 5CEE 3195)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x39BE2D725CEE3195 2009-05-21 [SC]
     Key fingerprint = D2FB 633A DDC2 0485 CBCE 6D12 39BE 2D72 5CEE 3195
uid  [ unknown] Daniel Baumann <daniel@127011.net>
uid  [ unknown] Daniel Baumann <daniel@undebian.org>
uid  [ unknown] Daniel Baumann <daniel@debian-unofficial.org>
uid  [ unknown] Daniel Baumann <daniel@unable-to-package.org>
uid  [ unknown] Daniel Baumann <daniel.baumann@panthera-systems.net>
uid  [ unknown] Daniel Baumann <daniel@free-law.ch>
uid  [ unknown] Daniel Baumann <mail@daniel-baumann.ch>
uid  [ unknown] Daniel Baumann <daniel@debian.org>
sub  rsa4096/0x2E86B0C2E7D77F65 2009-05-21 [E]
     Key fingerprint = 205A 272D 2838 238C 3058 C278 2E86 B0C2 E7D7 7F65
```

Key 2009-10-03 (9880 21A9 64E6 EA7D)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x988021A964E6EA7D 2009-10-03 [SC]
     Key fingerprint = 1046 0DAD 7616 5AD8 1FBC 0CE9 9880 21A9 64E6 EA7D
uid  [ unknown] Debian CD signing key <debian-cd@lists.debian.org>
```

Key 2011-01-05 (DA87 E80D 6294 BE9B)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0xDA87E80D6294BE9B 2011-01-05 [SC]
     Key fingerprint = DF9B 9C49 EAA9 2984 3258 9D76 DA87 E80D 6294 BE9B
uid  [ unknown] Debian CD signing key <debian-cd@lists.debian.org>
sub  rsa4096/0x642A5AC311CD9819 2011-01-05 [E]
     Key fingerprint = 47A8 EA16 451B F5C9 B691 5C64 642A 5AC3 11CD 9819
```

Key 2011-03-09 (6F95 B499 6CA7 B5A6)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2012, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x6F95B4996CA7B5A6 2011-03-09 [SC] [expired: 2021-02-01]
     Key fingerprint = 696F 95F0 88E4 D359 947F 7AEB 6F95 B499 6CA7 B5A6
uid  [ expired] Debian Live Signing Key <debian-live@lists.debian.org>
```

Key 2013-05-06 (510A D6B9 AD11 CF6A)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2013, according to the INTERNET ARCHIVE.


```
pub  rsa4096/0x510AD6B9AD11CF6A 2013-05-06 [SC]
     Key fingerprint = 1E4F 435C 4E9A 42B3 D9DF BE3A 510A D6B9 AD11 CF6A
uid  [ unknown] Debian Live Signing Key (2013) <debian-live@lists.debian.org>
sub  rsa4096/0x4E534D59B72E3E00 2013-05-06 [E]
     Key fingerprint = 407B 17AD 8CD1 B9D3 6891 262B 4E53 4D59 B72E 3E00
```

Key 2014-01-03 (1239 00F2 A9B2 6DF5)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2014, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x123900F2A9B26DF5 2014-01-03 [SC] [expires: 2025-01-01]
     Key fingerprint = 8A36 A2E8 91A5 C2A9 0DEB 7A8B 1239 00F2 A9B2 6DF5
uid  [ unknown] Live Systems Project <debian-live@lists.debian.org>
sub  rsa4096/0xA1A89023D0125917 2014-01-03 [E] [expires: 2025-01-01]
     Key fingerprint = A9E3 8E70 E798 7E03 285E D9C2 A1A8 9023 D012 5917
```

Key 2014-04-15 (4246 8F40 09EA 8AC3)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2014, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x42468F4009EA8AC3 2014-04-15 [SC]
     Key fingerprint = F41D 3034 2F35 4669 5F65 C669 4246 8F40 09EA 8AC3
uid  [ unknown] Debian Testing CDs Automatic Signing Key <debian-cd@lists.debian.org>
sub  rsa4096/0x0C5470136BD05CFB 2014-04-15 [E]
     Key fingerprint = AEE9 9CA7 0C3E C4B3 1C75 2843 0C54 7013 6BD0 5CFB
```

2.4 GITHUB

2.4.1 Background

GITHUB is a commercial GIT repository hosting service company founded in 2008. It was purchased by MICROSOFT in 2016.[1]

2.4.2 History

2008. GITHUB founded in San Francisco.[1]

2008-03-10. GITHUB parent company LOGICAL AWESOME, LLC registered in San Francisco by Chris Wanstrath.^{2.4.1}

2008-05-14. First snapshot of the <https://github.com> website on the INTERNET ARCHIVE.^{2.4.2}

2017-08-16. Creation date of the `4AEE 18F8 3AFD EB23` public key according to itself.

2017-11-14. Date of INTERNET ARCHIVE snapshot containing an early link to <https://github.com/web-flow.gpg> from a page on the help.github.com domain.^{2.4.3} Also the date of a post by GITHUB user jonathancross^{2.4.4} observing that the `4AEE 18F8 3AFD EB23` key appears to be a new feature^{2.4.5}:

Yeah, just experimented and saw the same thing. Strange new “feature” of GitHub it seems.

2018-06-04. First snapshot of the `4AEE 18F8 3AFD EB23` public key <https://github.com/web-flow.gpg> on the INTERNET ARCHIVE.^{2.4.6}

2021-05-25. Public key `4AEE 18F8 3AFD EB23` fingerprint explicitly published at GITHUB documentation website.^{2.4.7}

2.4.3 Public Key Details

2.4.3.1 Web-flow commit signing (`4AEE 18F8 3AFD EB23`)

As of 2021-07-19, when a user logs into github.com and creates a GIT commit through a web browser, GITHUB will automatically sign the commit against a GPG key^{2.4.8} with the fingerprint:

```
pub  rsa2048/0x4AEE18F83AFDEB23 2017-08-16 [SC]
     Key fingerprint = 5DE3 E050 9C47 EA3C F04A 42D3 4AEE 18F8 3AFD EB23
uid  [ unknown] GitHub (web-flow commit signing) <noreply@github.com>
```

This key is available for download at GITHUB's documentation website at <https://github.com/web-flow.gpg>.^{2.4.9} This particular link as well as the full key fingerprint was added to the GITHUB documentation repository in a commit dated 2021-05-25^{2.4.10}.

2.4.1. See <https://businesssearch.sos.ca.gov/Document/RetrievePDF?Id=200807010145-721605> and <https://businesssearch.sos.ca.gov/Document/RetrievePDF?Id=200807010145-2544282> from https://opencorporates.com/companies/us_ca/200807010145.

2.4.2. See <https://web.archive.org/web/20080514210148/http://github.com/>.

2.4.3. See <https://web.archive.org/web/20171114055613/https://help.github.com/articles/about-gpg/>.

2.4.4. Key fingerprint `C0C0 7613 2FFA 7695`. Key at <https://github.com/jonathancross.gpg>.

2.4.5. <https://github.com/keepassxreboot/keepassxc/issues/1183#issuecomment-344386172>.

2.4.6. <https://web.archive.org/web/20180604123146/https://github.com/web-flow.gpg>.

2.4.7. See <https://github.com/github/docs/commit/c4e1cb7a97704f0d90c0d6ed7e52d72b1e4946c1>.

2.4.8. See https://reboil.com/res/2021/txt/20210719_4AEE18F83AFDEB23..github.asc or <https://github.com/web-flow.gpg>.

2.4.9. See <https://docs.github.com/en/github/authenticating-to-github/managing-commit-signature-verification/about-commit-signature-verification>.

2.4.10. See <https://github.com/github/docs/commit/c4e1cb7a97704f0d90c0d6ed7e52d72b1e4946c1>.

2.5 RASPIBLITZ

2.5.1 Background

RASPIBLITZ is a software package designed to facilitate operation of a LIGHTNING NETWORK and BITCOIN node. The software is version controlled using GIT, with the main git repository available at GITHUB,^{2.5.1} As of 2021-07-18, the principal maintainer appears to be CHRISTIAN “ROOTZOL” ROTZOLL^{2.5.2}.

2.5.2 History

- 2019-09-03.** The creation date of rootzol's `1C73 060C 7C17 6461` public key.
- 2019-09-05.** ROOTZOL added their public key fingerprint `1C73 060C 7C17 6461` to the FAQ of the RASPIBLITZ GITHUB repository.^{2.5.3} They linked their `keybase.io` page as a source of the public key.
- 2020-10-31.** The first snapshot of the `raspi blitz.org` website appeared on the Internet Archive.^{2.5.4}
- 2021-02-07.** Andreas Antonopoulos posted a YouTube video identifying RASPIBLITZ as a popular Bitcoin full node software package.^{2.5.5}
- 2021-05-18.** ROOTZOL added their public key fingerprint `1C73 060C 7C17 6461` to the README of the RASPIBLITZ GITHUB repository.

2.5.3 Public Key Details

2.5.3.1 CHRISTIAN “ROOTZOL” ROTZOLL (`1C73 060C 7C17 6461`)

ROOTZOL's PGP key^{2.5.6} may be downloaded from their Keybase page.^{2.5.7} Their fingerprint information is as follows:

```
pub  rsa4096/0x1C73060C7C176461 2019-09-03 [C]
      Key fingerprint = 92A7 46AE 33A3 C186 D014 BF5C 1C73 060C 7C17 6461
uid  [ unknown] Christian Rotzoll <christian@rotzoll.de>
sub  rsa4096/0xAA9DD1B5CC5647DA 2019-09-03 [S] [expires: 2021-10-21]
sub  rsa4096/0xD40D94E6C7C9B4D9 2019-09-03 [E] [expires: 2021-10-21]
sub  rsa4096/0x1C29DC2F8D764F9A 2019-09-03 [A] [expires: 2021-10-21]
```

2.5.1. See <https://github.com/rootzoll/raspi blitz>.

2.5.2. Their public key `0x1c73060c7c176461` is available at: <https://keybase.io/rootzoll>.

2.5.3. See <https://github.com/rootzoll/raspi blitz/commit/75ebdd8d571cccc427b5d023a25c6e2e9e8a2da2>.

2.5.4. See <https://web.archive.org/web/20201031223643/https://raspi blitz.org/>.

2.5.5. See <https://www.youtube.com/watch?v=AXUfwvhr3lg&t=26m27s>.

2.5.6. See https://reboil.com/res/2021/txt/20210719_0x1C73060C7C176461...raspi blitz_rootzol.asc

2.5.7. See https://keybase.io/rootzoll/pgp_keys.asc.

2.6 SATOSHI LABS

2.6.1 Background

SATOSHI LABS is a company that produces cryptocurrency hardware wallets called TREZOR.^{2.6.1} These devices enable a user to privately manage their private keys necessary to create transactions. Publishing transactions and viewing current balances typically requires software running on a computer connected to the internet. SATOSHI LABS uses an OpenPGP key to sign these software packages published on their website <https://trezor.io>.

SATOSHI LABS was founded in 2013 by MAREK “SLUSH” PALATINUS, PAVOL “STICK” RUSNÁK, and ALENA VRANOVA.^{2.6.2} It is based in Prague, Czech Republic.

As of 2022-01-03, the primary TREZOR program requiring verification is TREZOR SUITE.

2.6.2 History

2012-03-07. Creation date of PAVOL RUSNÁK’s personal PGP key (91F3 B339 B9A0 2A3D).

2014-07-18. First snapshot of <https://mytrezor.com> appears on the INTERNET ARCHIVE.^{2.6.3}

2017-01-11. mytrezor.com, buytrezor.com, and other domains migrated to <https://trezor.io>.^{2.6.4}

2017-01-28. The first snapshot of <https://trezor.io> appears on the INTERNET ARCHIVE.^{2.6.5}

2020-10-20. Creation date of the 2020 signing key (26A3 A566 62F0 E7E2).

2021-01-04. Creation date of the 2021 signing key (E21B 6950 A2EC B65C).

2021-07-14. TREZOR SUITE launched^{2.6.6} in order to replace an older web wallet implementation.^{2.6.7}

2.6.3 Public Key Details

2.6.3.1 PAVOL RUSNÁK (91F3 B339 B9A0 2A3D)

A key^{2.6.8} used by a developer named PAVOL “STICK” RUSNÁK.^{2.6.9} This key has been used to sign TREZOR software in the past^{2.6.10} such as TREZOR BRIDGE^{2.6.11} and other various GITHUB commits.

```
pub  rsa4096/0x91F3B339B9A02A3D 2012-03-07 [SC] [expires: 2022-01-16]
    Key fingerprint = 86E6 792F C27B FD47 8860 C110 91F3 B339 B9A0 2A3D
uid      [ unknown] Pavo1 Rusnák <pavo1@rusnak.io>
uid      [ unknown] Pavo1 Rusnák <stick@gk2.sk>
uid      [ unknown] Pavo1 Rusnák <prusnak@opensuse.org>
uid      [ unknown] Pavo1 Rusnák <stick@satoshilabs.com>
uid      [ unknown] [jpeg image of size 2449]
sub  rsa4096/0x22AF226D38DC1F4D 2012-03-07 [E] [expires: 2023-01-08]
    Key fingerprint = E177 6F65 0601 E596 9E7F 9E25 22AF 226D 38DC 1F4D
```

2.6.3.2 2020 Signing Key (26A3 A566 62F0 E7E2)

A key^{2.6.12} used to sign the software required by a PC to communicate with the TREZOR product line. Expired as of 2021-01-01.

^{2.6.1.} Company website: <https://satoshilabs.com/>.

^{2.6.2.} See <https://web.archive.org/web/20140627154535/http://satoshilabs.com/team/>.

^{2.6.3.} See <https://web.archive.org/web/20140718104157/https://mytrezor.com/>.

^{2.6.4.} See <https://web.archive.org/web/20201111170337/https://blog.trezor.io/new-trezor-io-55cf687c88d5?gi=3481ee5b4637>.

^{2.6.5.} See <https://web.archive.org/web/20170128023418/https://trezor.io/>.

^{2.6.6.} See <https://blog.trezor.io/trezor-suite-launches-8958c1d37d33>.

^{2.6.7.} See <https://github.com/trezor/trezor-graveyard>.

^{2.6.8.} Download key at <https://rusnak.io/public/pgp.txt>.

^{2.6.9.} Twitter: <https://twitter.com/pavolrusnak>.

^{2.6.10.} See <https://github.com/trezor/trezord-go/issues/211>.

^{2.6.11.} See <https://github.com/trezor/webwallet-data/tree/master/bridge>.

^{2.6.12.} Download key at <https://trezor.io/security/satoshilabs-2020-signing-key.asc>.

```
pub  rsa4096/0x26A3A56662F0E7E2 2020-10-20 [SC] [expired: 2021-01-01]
     Key fingerprint = 5406 7D8B BF00 5541 81B5 AB8F 26A3 A566 62F0 E7E2
uid  [ expired] SatoshiLabs 2020 Signing Key
```

2.6.3.3 2021 Signing Key (E21B 6950 A2EC B65C)

A key^{2.6.13} used to sign the software required by a PC to communicate with the Trezor product line.

```
pub  rsa4096/0xE21B6950A2ECB65C 2021-01-04 [SC]
     Key fingerprint = EB48 3B26 B078 A4AA 1B6F 425E E21B 6950 A2EC B65C
uid  [ unknown] SatoshiLabs 2021 Signing Key
```

^{2.6.13}. Download key at <https://trezor.io/security/satoshilabs-2021-signing-key.asc> .

Appendix A

How Public Key Cryptography Works

This appendix describes in more detail how public key cryptography works.

Appendix B

How to use GNUPG

This appendix describes in more detail how to use GNUPG. Examples assume use of GNUPG version 2.2.12.

B.1 Definitions

Long ID. A 16-digit hexadecimal number used to identify a public key, e.g. `A0A2 95AB DC34 69C9`. Its hexadecimal nature may be emphasized by prepending the string with the “0x” prefix and omitting spaces, e.g. `0xA0A295ABDC3469C9`.^{B.1.1} GNUPG is not particular about whether letters in the Long ID are upper or lowercase, so `0xa0a295abdc3469c9` is also acceptable.

Short ID. An 8-digit hexadecimal number similar to a **Long ID**. Use of Short IDs is not recommended because, as of 2021, generating multiple public keys with matching Short IDs requires a negligible amount of computing power.^{B.1.2}

Remark B.1.1. Example code is sometimes given in the form of a BASH script. Such scripts usually have a first line like `#!/usr/bin/env bash` that tell your interpreter to execute the lines that follow as BASH commands. This is useful from a typography standpoint because often the length of GNUPG commands can exceed the recommended character limit for human readability.^{B.1.3} This document will attempt to limit line widths in code examples to approximately 80 characters.

B.2 Useful Commands

B.2.1 Obtaining keys

B.2.1.1 Import a public key

The `$ gpg --import key.asc` command may be used to import a file named “key.asc”. If the `$ gpg --import` command by itself is run and a clipboard program is available (e.g. copy/paste), then pasting the text of a public key into the shell followed by pressing `ctrl-d` (i.e. providing an “end of transmission” character^{B.2.1}) will tell `gpg` to process the pasted text.

B.2.1.2 Download from a keyserver

The `$ gpg --receive-keys` command can be used as shown in the example below to download a public key (e.g. `4246 8F40 09EA 8AC3`) from a keyserver (e.g. `keyserver.ubuntu.com`).

```
$ gpg --receive-keys --keyserver keyserver.ubuntu.com 42468f4009ea8ac3
gpg: key 0x42468F4009EA8AC3: public key "Debian ... <debian-cd@lists.debian.org>" imported
gpg: Total number processed: 1
gpg:                imported: 1
```

B.1.1. See <https://stackoverflow.com/questions/2670639/why-are-hexadecimal-numbers-prefixed-with-0x>.

B.1.2. See <https://security.stackexchange.com/questions/84280/>.

B.1.3. EMACS, for example, defaults to wrapping columns of text to 70. See <https://emacs.stackexchange.com/questions/36118/>.

B.2.1. See <https://unix.stackexchange.com/a/110248>.

As of 2022-01-14, few keyserver provide full public keys due to an unsolved certificate spam problem.^{B.2.2}

- keyserver.ubuntu.com - Provides full keys.
- keyring.debian.org - Provides full keys of DEBIAN developer and maintainers.
- keys.openpgp.org - Provides keys without user IDs unless key owner authenticates themselves via the user ID email address.

B.2.2 Analyzing keys

B.2.2.1 View public key fingerprint

- Show fingerprints of the primary key and subkeys . The example below shows the primary fingerprint in **red**, the Long ID colored in **brown**, user IDs in **blue**, and fingerprints of subkeys **dark green**.

```
$ gpg --fingerprint 0xa0a295abdc3469c9
pub  rsa4096/0xA0A295ABDC3469C9 2017-10-11 [C] [expires: 2022-07-08]
    Key fingerprint = 3457 A265 922A 1F38 39DB 0264 A0A2 95AB DC34 69C9
uid  [ultimate] Steven Sandoval <baltakatei@gmail.com>
uid  [ultimate] Steven Sandoval <baltakatei@alumni.stanford.edu>
sub  rsa4096/0x6DD7D496916A1253 2018-05-16 [E] [expires: 2022-07-07]
    Key fingerprint = 5E55 5FC6 1C85 871E 813B 5BCF 6DD7 D496 916A 1253
sub  rsa4096/0x57DA57D9517E6F86 2018-05-16 [S] [expires: 2022-07-07]
    Key fingerprint = 38F9 6437 C83A C88E 28B7 A952 57DA 57D9 517E 6F86
sub  rsa4096/0x5F9D26B9A598A2D3 2018-05-16 [A] [expires: 2022-07-07]
    Key fingerprint = EDCA 7EE7 D09E 7F2E 1DF6 A229 5F9D 26B9 A598 A2D3
```

B.2.3 Sending keys

B.2.3.1 Export public key

- Export public key according to last 16 characters of public key fingerprint (i.e. “long ID”, e.g. **A0A2 95AB DC34 69C9**).

```
$ gpg --export --output /tmp/key 0xa0a295abdc3469c9.
```

- Export the smallest key possible. Useful to strip key of signatures except for self-signatures. This creates an ASCII-armored^{B.2.3} text file named `pubkey.asc` in the `/tmp` directory.

```
#!/usr/bin/env bash
gpg --export --export-options export-minimal \
--armor \
--output /tmp/pubkey.asc \
0xa0a295abdc3469c9
```

B.2.4 Creating keys

B.2.4.1 Using default settings

Running `$ gpg --gen-key` will guide the user to creating a key with default settings.

B.2.4.2 With subkeys

The `$ gpg --expert --full-gen-key` command in combination with some modifications to the configuration file `~/.gnupg/gpg.conf` may be used to create an OpenPGP key with subkeys. Subkeys are useful since their private components can be loaded onto a smartcard while keeping the primary key offline, available to create new subkeys. This may be desirable if a primary key is intended to be used over a long time period and the risk of losing an online defaultly configured key is unacceptable. Please see the article by Thierry Thuron titled “OpenPGP - The Almost Perfect Key Pair” for a useful procedure.^{B.2.4}

^{B.2.2.} Hansen, Robert J. “SKS Keyserver Network Under Attack”. 2019-06-29. <https://gist.github.com/rjhansen/67ab921ffb4084c865b3618d6955275f>.

^{B.2.3.} See <https://crypto.stackexchange.com/questions/91984/why-use-ascii-armor-for-file-encryption>.

^{B.2.4.} Thuron, Thierry. “OpenPGP - The Almost Perfect Key Pair”. 2017-10-13. Eleven Labs Blog. <https://blog.elevenlabs.com/en/openpgp-almost-perfect-key-pair-part-1/>.

Bibliography

[1] Steve Lohr . Microsoft Buys GitHub for \$7.5 Billion, Moving to Grow in Coding's New Era. *New York Times*, 2018.

Index

Andresen, Gavin	10	Keys	
Antonopoulos, Andreas	19	People	
Bitcoin Core	10–11	van der Laan, Wladimir J.	
Cross, Jonathan	18	0x74810B012346C9A6	11
DSA, algorithm		0x90C8019E36C2E964	10
weakness	11	Logical Awesome, LLC	18
GitHub	18	Microsoft	18
Keys		Nakamoto, Satoshi	10
Organizations		Organizations	
Cryptomator		Bitcoin Foundation	11
0x509C9D6334C80F11	12	Palatinus, Marek “Slush”	20
0x615D449FE6E6A235	13	RASPIBLITZ	19–?
GitHub		Rotzoll, Christian “rootz01”	19
0x4AEE18F83AFDEB23	18	Rusnák, Pavol “Stick”	20
Satoshi Labs		Satoshi Labs	20–21
2020 Signing Key		Slush (SATOSHI LABS developer)	20
0x26A3A56662F0E7E2	20	Software	
2021 Signing Key		RASPIBLITZ	19–?
0xE21B6950A2ECB65C	21	Software	
People		Bitcoin	10, 19
Andresen, Gavin		Lightning Network	19
0x29D9EE6B1FC730C1	11	Stick (SATOSHI LABS developer)	20
Nakamoto, Satoshi		Todd, Peter	10
0x18C09E865EC948A1	11	Trezor	20
Rotzoll, Christian “rootz01”		van der Laan, Wladimir J.	10
0x1C73060C7C176461	19	Vranova, Alena	20
Rusnák, Pavol “Stick”		Wanstrath, Chris	18
0x91F3B339B9A02A3D	20		