

Notable Public Keys

STEVEN BALTAKATEI SANDOVAL

Email: `baltakatei@gmail.com`

Web: `https://reboil.com`

Front Matter

This book is copyright ©2021 by Steven Baltakatei Sandoval. This book is licensed under Creative Commons Attribution-ShareAlike 4.0 International License (CC BY-SA 4.0):

<https://creativecommons.org/licenses/by-sa/4.0/>

The book is available as source code in a `git` repository available at:

<https://gitlab.com/baltakatei/npk.git>

This book was typeset using **TEX_{MACS}** version 2.1.1.

Fonts used include **Linux Libertine**.

This book was rendered on 2022-03-12T12:44:19+0000.

Table of contents

Front Matter	3
1 Trust through Stories	9
1.1 Summary	9
1.2 Background	9
1.3 Purpose	9
2 List of Public Keys	11
2.1 BITCOIN CORE	12
2.1.1 Background	12
2.1.2 History	12
2.1.3 Public Key Details	13
2.1.3.1 Binary Signing Keys (v0.22.0–)	13
2.1.3.2 Binary Signing Key (v0.11.0–v0.21.2) (90C8 019E 36C2 E964)	13
2.1.3.3 Binary Signing Key (v0.9.3–v0.10.2) (7481 0B01 2346 C9A6)	13
2.1.3.4 Binary Signing Key (v0.8.6–v0.9.2.1) (29D9 EE6B 1FC7 30C1)	13
2.1.3.5 SATOSHI NAKAMOTO (18C0 9E86 5EC9 48A1)	14
2.2 CRYPTOMATOR	15
2.2.1 Background	15
2.2.2 History	15
2.2.3 Public Key Details	15
2.2.3.1 Binary signing key (–v1.5.7) (509C 9D63 34C8 0F11)	15
2.2.3.2 Binary signing key (v1.5.8–) (615D 449F E6E6 A235)	16
2.3 DEBIAN	17
2.3.1 Background	17
2.3.2 History	17
2.3.3 Public Key Details	17
2.3.3.1 Installation Image Signature Keys	17
2.3.3.2 Verbose key details	18
Key 1999-01-30 (7C3B 7970 88C7 C1F7)	18
Key 2000-09-16 (72FD C205 F6A3 2A8E)	18
Key 2004-06-20 (F82E 5CC0 4B2B 2B9E)	19
Key 2009-05-21 (39BE 2D72 5CEE 3195)	19
Key 2009-10-03 (9880 21A9 64E6 EA7D)	19
Key 2011-01-05 (DA87 E80D 6294 BE9B)	19
Key 2011-03-09 (6F95 B499 6CA7 B5A6)	19
Key 2013-05-06 (510A D6B9 AD11 CF6A)	19
Key 2014-01-03 (1239 00F2 A9B2 6DF5)	20
Key 2014-04-15 (4246 8F40 09EA 8AC3)	20
2.4 ELECTRUM	21
2.4.1 Background	21
2.4.2 History	21
2.4.3 Public Key Details	21
2.4.3.1 ELECTRUM client release signing key (v1.7–) (2BD5 824B 7F94 70E6)	21
2.4.3.2 ELECTRUMX server commit key (E7B7 48CD AF5E 5ED9)	21
2.5 GITHUB	22

2.5.1	Background	22
2.5.2	History	22
2.5.3	Public Key Details	22
2.5.3.1	Web-flow commit signing (4AEE 18F8 3AFD EB23)	22
2.6	RASPIBLITZ	23
2.6.1	Background	23
2.6.2	History	23
2.6.3	Public Key Details	23
2.6.3.1	CHRISTIAN “ROOTZOL” ROTZOLL (1C73 060C 7C17 6461)	23
2.7	SATOSHI LABS	24
2.7.1	Background	24
2.7.2	History	24
2.7.3	Public Key Details	24
2.7.3.1	PAVOL RUSNÁK (91F3 B339 B9A0 2A3D)	24
2.7.3.2	2020 Signing Key (26A3 A566 62F0 E7E2)	25
2.7.3.3	2021 Signing Key (E21B 6950 A2EC B65C)	25
2.8	TAILS	26
2.8.1	Background	26
2.8.2	History	26
2.8.3	Public Key Details	26
2.8.3.1	Signing key (2015–) (DBB8 02B2 58AC D84F)	26
2.8.3.2	Signing key (2010–2015) (1202 821C BE2C D9C1)	27
2.8.3.3	Mailing list key (2009–) (1D29 75ED F93E 735F)	27
2.9	TOR BROWSER	28
2.9.1	Background	28
2.9.2	History	28
2.9.3	Public Key Details	28
2.9.3.1	Release Signing Key (2015–) (4E2C 6E87 9329 8290)	28
2.10	VERACRYPT	29
2.10.1	Background	29
2.10.2	History	29
2.10.3	Public Key Details	29
2.10.3.1	Signing key (2018–) (821A CD02 680D 16DE)	29
2.10.3.2	Signing key (2014–2018) (EB55 9C7C 54DD D393)	30
2.11	YOUTUBE-DL	31
2.11.1	Background	31
2.11.2	History	31
2.11.3	Public Key Details	31
2.11.3.1	Binary signing key. SERGEY M. (2C39 3E0F 18A9 236D)	31
2.11.3.2	Binary signing key. PHILIPP HAGEMEISTER (F5EA B582 FAFB 085C)	31
2.11.3.3	Binary signing key. PHILIPP HAGEMEISTER (DB4B 54CB A482 6A18)	32
2.11.3.4	Binary signing key. FILIPPO VALSORDA (EBF0 1804 BCF0 5F6B)	32
Appendix A How Public Key Cryptography Works		33
Appendix B How to use GnuPG		35
B.1	Definitions	35
B.2	Useful Commands	35
B.2.1	Obtaining keys	35
B.2.1.1	Import a public key	35
B.2.1.2	Download from a keyserver	35
B.2.2	Analyzing keys	36
B.2.2.1	View public key fingerprint	36
B.2.3	Sending keys	36
B.2.3.1	Export public key	36
B.2.4	Creating keys	36

B.2.4.1 Using default settings 36

B.2.4.2 With subkeys 36

Bibliography 37

Index 39

Chapter 1

Trust through Stories

1.1 Summary

This book contains stories about where certain public keys came from and a little about the people who use them.

Some people use public key cryptography to digitally sign their works. They do this so others can prove where copies of such works came from. Usually, digital tools automatically verify these digital signatures so people don't have to manually. However, in order to verify such tools, at some point a person must verify at least one digital signature for themselves.

1.2 Background

As of 2022, most people, if they worry at all about where they download their software from, usually only check that there is a padlock symbol next to the URL in their browser. Thanks to the efforts of LET'S ENCRYPT and other companies promoting use of digital signature technology known as TLS (a.k.a. SSL, HTTPS), most people can rely on that padlock symbol, provided they pay attention to the base domain of the URL (i.e. the **“google.com”** of **“https://mail.google.com”**).

TLS works by having a user's web browser come installed with a set of public keys whose private keys are kept secure by IT professionals trusted by governments. These IT people are known as “certificate authorities” (CA). Whenever a webmaster wants to authenticate themselves to visitors to their website, the webmaster may create their own public-private keypair and ask a CA to digitally sign their public key. Then, whenever a visitor's web browser downloads a webpage, the server uses the webmaster's private key to digitally sign the webpage. The web browser can then download the server's public key, see that it is signed by a CA whose public key it already knows about and trusts. This is the cryptographically-secured process that occurs whenever a web browser's padlock symbol indicates a secure TLS connection.

However, for paranoid technically-minded people who want to take precautions against servers being hacked, CA private keys being compromised, or some form of man-in-the-middle attack, sometimes software developers use their own digital certificate systems to authenticate themselves. One such system is OPENPGP. Instead of relying upon CAs trusted by governments, each software developer is their own CA. Unlike with TLS and web browsers, users who wish to verify digital signatures on programs made by such developers must have some trusted means of identifying and acquiring the developers' public keys. With OPENPGP, although it is possible in theory to create and maintain a “Web of Trust” by having key owners regularly sign eachothers' keys based upon their personal relationships with one another, in practice this method of establishing trust is outcompeted by the simplicity of using TLS; if the stakes of misidentifying a team member on a project are high enough, it is much simpler to simply meet in-person.

1.3 Purpose

That said, the purpose of this book is to provide you, reader, a means of identifying public keys used to sign notable software and data. Notability is defined and applied as in WIKIPEDIA: it is a test to determine whether a chapter about an entity's public keys should be included. Where potential for confusion exists around the identity of a notable entity that maintains a public key, this book should identify that key.

This document is a tertiary reference meant to paint a narrative about how and by whom a public key is used. Often public keys are secured by individual software developers and used to sign commits made in their version control systems. Some public keys are used by an individual but to represent an entire company or project. Although most public keys in this book are OPENPGP keys compatible with the GnuPG program, some public keys may use other systems or protocols such as those in TLS certificates, SSH key pairs, or cryptocurrency wallets^{1.3.1}, as long as they are notable.

This book started as a set of personal notes I began maintaining in 2018 to help me verify software packages that I use. In 2021 I decided to share these notes in book-form with the help of the GNU $\text{\TeX}_{\text{MACS}}$ typesetting program (mainly for its indexing and open-source nature). As of 2022, the method of verification of key notability (me, `AOA2 95AB DC34 69C9`, scanning the web for fingerprints and keys of programs I use) is not scalable. However, this book uses the GIT version control system and lives in a GITLAB repository so additional collaborators (you) could help this book grow.

1.3.1. E.g.: The address of the first spendable Bitcoin. See <https://chainflyer.bitflyer.com/Block/Height/1>.

Chapter 2

List of Public Keys

Each section in this chapter contains a story about a person or organization that uses a public-private key pair. Each story consists of some brief background information, a history of notable events, and public key information. Public keys are usually identified through key fingerprints. Links to public keys are made available where possible^{2.0.1}.

^{2.0.1}. A set of minimal copies of GNUPG public keys is available in the GIT repository of this book in `ref/pgp_keys/`. File names contain the full 160-bit hexadecimal fingerprint.

2.1 BITCOIN CORE

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.1.1 Background

BITCOIN CORE^{2.1.1} is the “reference implementation” of the BITCOIN protocol. It is maintained by a group of people who have become known as the BITCOIN CORE developers.

Early in the blockchain's history, the software that verified transactions against balances of previous transactions was a WINDOWS executable known as BITCOIN. The initial release of this software was by an entity that called themselves SATOSHI NAKAMOTO. Satoshi later gave up the code maintainer role of the project. The person who subsequently gained control was a person named GAVIN ANDRESEN. The software was rebranded from BITCOIN to BITCOIN CORE at version 0.9.0.^{2.1.2} A developer named WLADIMIR J. VAN DER LAAN became owner of the OPENPGP signing keys of the reference implementation starting at version 0.9.3. VAN DER LAAN originally used a personal key (7481 0B01 2346 C9A6) to sign binaries but later created a dedicated key (90C8 019E 36C2 E964) to sign binaries. In 2021, binaries were instead signed by a group of people each with their own personal key.

There exist various dubious theories regarding PGP key use by SATOSHI NAKAMOTO.^{2.1.3} The most likely candidate (18C0 9E86 5EC9 48A1) is one signed by BITCOIN CORE developers PETER TODD (7FAB 1142 67E4 FA04) and WLADIMIR J. VAN DER LAAN (7481 0B01 2346 C9A6).

2.1.2 History

2011-08-24. Creation date of VAN DER LAAN's personal signing key 7481 0B01 2346 C9A6.

2011-12-15. Creation date of ANDRESEN's dedicated code signing key 29D9 EE6B 1FC7 30C1.

2013-03-23. Earliest snapshot of the <https://bitcoin.org> website on the INTERNET ARCHIVE.^{2.1.4} It is a redirect to <https://bitcoin.org/en>.

2013-04-11. Earliest snapshot of the <https://bitcoincore.org> website on the INTERNET ARCHIVE.^{2.1.5}

2013-07-27. Earliest snapshot of main GITHUB repository at <https://github.com/bitcoin/bitcoin> on the INTERNET ARCHIVE.^{2.1.6}

2014-03-19. The reference client rebranded from BITCOIN to BITCOIN CORE.

2014-04-08. GAVIN ANDRESEN steps down as lead developer. Hands over role to WLADIMIR J. VAN DER LAAN.^{2.1.7} ANDRESEN maintains commit privileges to the GITHUB repository.

2015-06-24. Creation date of VAN DER LAAN's dedicated code signing key 90C8 019E 36C2 E964.

2016-05-02. GAVIN ANDRESEN's commit privileges revoked by other BITCOIN CORE developers after ANDRESEN published a blog post claiming CRAIG WRIGHT was SATOSHI NAKAMOTO.^{2.1.8}

2021-09-13. BITCOIN CORE version 0.22.0 published with change to how binary releases are signed. Releases now signed by several individuals^{2.1.9} instead of VAN DER LAAN's dedicated code signing key 90C8 019E 36C2 E964.^{2.1.10}

2.1.1. Main website: <https://bitcoincore.org/>.

2.1.2. See <https://bitcoin.org/en/release/v0.9.0#rebranding-to-bitcoin-core>.

2.1.3. See <https://www.vice.com/en/article/jpgq3y/satoshis-pgp-keys-are-probably-backdated-and-point-to-a-hoax>.

2.1.4. See <https://web.archive.org/web/20130323195546/http://bitcoin.org/en>.

2.1.5. See <https://web.archive.org/web/20130411033932/http://bitcoincore.org/>.

2.1.6. See <https://web.archive.org/web/20130727135658/https://github.com/bitcoin/bitcoin>.

2.1.7. See <https://www.coindesk.com/gavin-andresen-steps-bitcoins-lead-developer>.

2.1.8. See <https://twitter.com/peterktodd/status/727078284345917441>, <https://laanwj.github.io/2016/05/06/hostility-scams-and-moving-forward.html>, <https://www.bbc.com/news/technology-36202904>, and <https://www.theguardian.com/technology/2016/may/06/bitcoin-project-blocks-out-gavin-andresen-over-satoshi-nakamoto-claims>.

2.1.9. For list of fingerprints, see <https://web.archive.org/web/20210725054312/https://github.com/bitcoin/bitcoin/blob/master/contrib/builder-keys/keys.txt>.

2.1.10. See <https://web.archive.org/web/20210926105351/https://bitcoincore.org/en/download/>; specifically “Linux verification instructions”.

2.1.3 Public Key Details

2.1.3.1 Binary Signing Keys (v0.22.0–)

Since the release of BITCOIN CORE version *0.22.0* on 2019-09-13, the SHA256SUMS file available at <https://bitcoincore.org/en/download> has been split into two files:

SHA256SUMS. Contains hashes of the binary executable files.

SHA256SUMS.asc. Contains multiple detached signatures from different public keys.

For version *0.22.0*, the fingerprints and primary UIDs of these signatures are in Table 2.1.1.

Fingerprint	UID Name
099B AD16 3C70 FBFA	Will Clark
0A41 BDC3 F4FA FF1C	Aaron Clauson (sipsorcery)
7481 0B01 2346 C9A6	Wladimir J. van der Laan
796C 4109 063D 4EAF	Jon Attack
4101 0811 2E7E A81F	Hennadii Stepanov (GitHub key)
8E42 5659 3F17 7720	Oliver Gugger
944D 35F9 AC3D B76A	Michael Ford (bitcoin-otc)
2EBB 056F D847 F8A7	Stephan Oeste (it)
C37B 1C1D 44C7 86EE	Duncan Dean
E13F C145 CD3F 4304	Antoine Poinot
D7CC 770B 81FD 22A8	Ben Carman
1756 5732 E08E 5E41	Andrew Chow (Official New Key)

Table 2.1.1. Fingerprints of OPENPGP keys that signed hashes of BITCOIN CORE v0.22.0 release files.

2.1.3.2 Binary Signing Key (v0.11.0–v0.21.2) (90C8 019E 36C2 E964)

This key^{2.1.11}, owned by WLADIMIR J. VAN DER LAAN, was used to sign BITCOIN CORE releases between versions *0.11.0* and *0.21.2*.

```
pub  rsa4096/0x90C8019E36C2E964 2015-06-24 [SC] [expired: 2022-02-10]
     Key fingerprint = 01EA 5486 DE18 A882 D4C2 6845 90C8 019E 36C2 E964
uid  [ expired] Wladimir J. van der Laan (Bitcoin Core binary...) <69ed48c5>
```

2.1.3.3 Binary Signing Key (v0.9.3–v0.10.2) (7481 0B01 2346 C9A6)

WLADIMIR VAN DER LAAN used his personal key^{2.1.12} to sign BITCOIN versions v0.9.3–v0.10.2.

```
pub  rsa2048/0x74810B012346C9A6 2011-08-24 [SC] [expires: 2027-02-08]
     Key fingerprint = 71A3 B167 3540 5025 D447 E8F2 7481 0B01 2346 C9A6
uid  [ unknown] Wladimir J. van der Laan <b64e04a4>
uid  [ unknown] Wladimir J. van der Laan <69ed48c5>
uid  [ unknown] Wladimir J. van der Laan <c7357718>
sub  rsa2048/0x69B4C4CDC628F8F9 2017-05-17 [A] [expires: 2027-02-08]
     Key fingerprint = 53D9 74DA OBAF FF22 B3A5 FB5C 69B4 C4CD C628 F8F9
sub  rsa2048/0xF69705ED890DE427 2011-08-24 [E]
     Key fingerprint = D01B 5D68 0154 44D2 71DA D33F F697 05ED 890D E427
sub  rsa2048/0x1E4AED62986CD25D 2017-05-17 [S] [expires: 2027-02-08]
     Key fingerprint = 9DEA E0DC 7063 249F B054 7468 1E4A ED62 986C D25D
```

2.1.3.4 Binary Signing Key (v0.8.6–v0.9.2.1) (29D9 EE6B 1FC7 30C1)

GAVIN ANDRESEN used this dedicated code-signing key^{2.1.13} to sign BITCOIN versions v0.8.6–v0.9.2.1. As of 2021-07-19, these versions and their signatures are available at <https://bitcoincore.org/bin/insecure/>.

2.1.11. See https://reboil.com/res/2021/txt/20210719_90C8019E36C2E964..bitcoin_vanderlaan.asc

2.1.12. See https://reboil.com/res/2021/txt/20210719_74810B012346C9A6..bitcoin_vanderlaan.asc

2.1.13. See https://reboil.com/res/2021/txt/20210719_29D9EE6B1FC730C1..bitcoin_andresen.asc

```

pub  rsa4096/0x29D9EE6B1FC730C1 2011-12-15 [SC]
     Key fingerprint = 2664 6D99 CBAE C9B8 1982 EF60 29D9 EE6B 1FC7 30C1
uid  [ unknown] Gavin Andresen (CODE SIGNING KEY) <84976526>
sub  rsa4096/0x1B7BFB457BF6E212 2013-11-01 [S]
     Key fingerprint = 3D22 F497 DEAE D078 18A2 219A 1B7B FB45 7BF6 E212
sub  rsa4096/0x36E924A98E30B3ED 2011-12-15 [E]
     Key fingerprint = DC9F CD02 AB25 5459 FDA8 7469 36E9 24A9 8E30 B3ED

```

2.1.3.5 SATOSHI NAKAMOTO (18C0 9E86 5EC9 48A1)

The dsa1024 algorithm this key^{2.1.14} uses is considered weak by the the NIST standard SP800-57 Part 1 Revision 5: *Recommendation for Key management*.^{2.1.15} The key offers only 80 bits of security against the possibility of impersonation via a brute force attack. Nevertheless, this key has a signature of BITCOIN CORE developer PETER TODD (7FAB 1142 67E4 FA04) dated 2013-10-12. TODD also committed the full fingerprint in a BITCOIN FOUNDATION document on 2013-04-26^{2.1.16}. This key also has a signature of BITCOIN CORE maintainer VLADIMIR J. VAN DER LAAN's personal key (7481 0B01 2346 C9A6) dated 2013-05-10, albeit revoked on 2016-05-02.

```

pub  dsa1024/0x18C09E865EC948A1 2008-10-30 [SC]
     Key fingerprint = DE4E FCA3 E1AB 9E41 CE96 CECB 18C0 9E86 5EC9 48A1
uid  [ unknown] Satoshi Nakamoto <6bab5993>
sig 3 0x18C09E865EC948A1 2008-10-30 Satoshi Nakamoto <6bab5993>
sig   0x74810B012346C9A6 2013-05-10 Wladimir J. van der Laan <c7357718>
sig 1 0x7FAB114267E4FA04 2013-10-12 Peter Todd <13866f62>
rev   0x74810B012346C9A6 2016-05-02 Wladimir J. van der Laan <c7357718>
     reason for revocation: User ID is no longer valid
sub  elg2048/0xCF1857E6D6AAA69F 2008-10-30 [E]
     Key fingerprint = EA4E 9C90 7F72 21B0 B37D 0940 CF18 57E6 D6AA A69F

```

^{2.1.14}. See https://reboil.com/res/2021/txt/20210719_18C09E865EC948A1..bitcoin_nakamoto.asc

^{2.1.15}. See <https://doi.org/10.6028/NIST.SP.800-57pt1r5>, table 2, page 54. dsa1024 keys have only offer 80 bits of security against brute force attacks.

^{2.1.16}. See <https://github.com/pmlaw/The-Bitcoin-Foundation-Legal-Repo/commit/fb70771a9927e04ebe5ae33c46ba6589a9703e40>.

2.2 CRYPTOMATOR

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.2.1 Background

CRYPTOMATOR^{2.2.1} is a cross-platform file storage privacy application. It permits storing files on a third-party file storage services (e.g. DROPBOX) in encrypted form and accessible to the user as a virtual mountable drive. In other words, CRYPTOMATOR acts as an encryption layer between a user and a file storage service. Compiled binary releases are available for WINDOWS, MACOS, LINUX, ANDROID, and IOS^{2.2.2}.

As of 2021-12-22, the latest version of CRYPTOMATOR is version 1.6.5 (*Hotfix*) available on GITHUB.^{2.2.3} Judging from commit signatures of the GITHUB repository^{2.2.4}, the main developers appear to be SEBASTIAN STENZEL (667B 866E A824 0A09) ARMIN SCHRENK (748E 55D5 1F5B 3FBC), and TOBIAS HAGEMANN (0x69CEFA519598989).

2.2.2 History

2015-01-01. First snapshot of <https://cryptomator.org> captured on the INTERNET ARCHIVE.^{2.2.5} Signature of latest version of CRYPTOMATOR (1.4.11) uses PGP key 509C 9D63 34C8 0F11.^{2.2.6}

2018-06-17. Binary signing PGP key 509C 9D63 34C8 0F11 published as GITHUB gist.^{2.2.7} Key used to sign CRYPTOMATOR versions prior to 1.5.8.

2020-09-01. Binary signing PGP key 615D 449F E6E6 A235 published as GITHUB gist.^{2.2.8} Key used to sign CRYPTOMATOR version 1.5.8 onward (as of 2021-12-22).

2020-09-02. Old binary signing PGP key 615D 449F E6E6 A235 signed by new PGP key 509C 9D63 34C8 0F11.^{2.2.9} Notice of revocation of old key and signing of new key by old key posted in GITHUB issue thread.^{2.2.10}

2.2.3 Public Key Details

2.2.3.1 Binary signing key (-v1.5.7) (509C 9D63 34C8 0F11)

PGP key used to sign compiled binary releases of CRYPTOMATOR prior to version 1.5.8.

```
pub  rsa4096/0x509C9D6334C80F11 2016-06-24 [SC] [revoked: 2020-08-18]
    Key fingerprint = 5054 3A3D A4B1 DB81 DA3E 79CB 509C 9D63 34C8 0F11
uid      [ revoked] Cryptobot (Release Manager) <d0228975>
```

2.2.1. Main website: <https://cryptomator.org/>.

2.2.2. See <https://cryptomator.org/downloads/>.

2.2.3. See <https://github.com/cryptomator/cryptomator/releases/tag/1.6.5>.

2.2.4. See <https://github.com/cryptomator/cryptomator>.

2.2.5. See <https://web.archive.org/web/20150101033915/http://cryptomator.org/>.

2.2.6. Signature file at: https://web.archive.org/web/20210502041159/https://dl.bintray.com/cryptomator/cryptomator/1.4.11/cryptomator-1.4.11-x86_64.AppImage.asc. Signed file at: https://web.archive.org/web/20210502115653/https://dl.bintray.com/cryptomator/cryptomator/1.4.11/cryptomator-1.4.11-x86_64.AppImage.

2.2.7. See <https://gist.github.com/cryptobot/8ccf8fd686d0c2d8381b69126bb3f2f8/9fdeef62bddf9edf7b73f61f42423f1f123d3218>.

2.2.8. See <https://gist.github.com/cryptobot/211111cf092037490275f39d408f461a/1a8e133a1d7e6ae4eb2bcc0830e4567393e5162a>.

2.2.9. See <https://gist.github.com/cryptobot/211111cf092037490275f39d408f461a/d416c6f0d35506116436cbe2f872baa217f3f72a>.

Verify with `$ gpg --import` and `$ gpg --list-signatures` to show the signature (highlighted):

```
pub  rsa4096/0x615D449FE6E6A235 2020-08-18 [SC] [expires: 2031-01-01]
    Key fingerprint = 5811 7AFA 1F85 B3EE C154 677D 615D 449F E6E6 A235
uid      [ unknown] Cryptobot <d0228975>
sig 3    0x615D449FE6E6A235 2020-08-18 Cryptobot <d0228975>
sig      0x509C9D6334C80F11 2020-09-02 Cryptobot (Release Manager) <d0228975>
```

2.2.10. See <https://github.com/cryptomator/cryptomator.github.io/issues/25#issuecomment-685308263>.

2.2.3.2 Binary signing key (v1.5.8-) (615D 449F E6E6 A235)

PGP key used to sign compiled binary releases of CRYPTOMATOR after version *1.5.8* (as of 2021-12-22). The key and fingerprint are available on the Linux download page.^{2.2.11}

```
pub  rsa4096/0x615D449FE6E6A235 2020-08-18 [SC] [expires: 2031-01-01]
     Key fingerprint = 5811 7AFA 1F85 B3EE C154 677D 615D 449F E6E6 A235
uid          [ unknown] Cryptobot <d0228975>
```

^{2.2.11.} See <https://web.archive.org/web/20211222094028/https://cryptomator.org/downloads/linux/thanks/#>.

2.3 DEBIAN

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.3.1 Background

DEBIAN^{2.3.1} is a free operating system from which many GNU/LINUX systems are derived. Such derived systems include UBUNTU, TAILS, KALI LINUX, and others.

DEBIAN is maintained by an association of developers who use GnuPG keys to sign announcements of software they contribute in order to protect against forgeries. A git repository containing GnuPG keyrings of DEBIAN keys is available at <https://salsa.debian.org/debian-keyring/keyring> or by installation of the `debian-keyring` package^{2.3.2} within a DEBIAN system.

The DEBIAN PROJECT was founded in 1993 by IAN ASHLEY MURDOCK. Various individuals have led the project since.^{2.3.3} As of 2021-09-25, the latest release of the operating system is called “DEBIAN 11 (BULLSEYE)”.

2.3.2 History

1993-08-16. The DEBIAN PROJECT officially founded by IAN ASHLEY MURDOCK.

1999-01-30. Creation date of the Debian CD signing key `7C3B 7970 88C7 C1F7`.

2000-09-16. Creation date of SANTIAGO GARCIA MANTINAN's key `72FD C205 F6A3 2A8E`.

2004-06-20. Creation date of DANIEL BAUMANN's key `F82E 5CC0 4B2B 2B9E`.

2009-10-03. Creation date of the Debian CD signing key `9880 21A9 64E6 EA7D`.

2011-01-05. Creation date of the Debian CD signing key `DA87 E80D 6294 BE9B`.

2014-04-15. Creation date of the Debian Testing CDs Automatic Signing Key `4246 8F40 09EA 8AC3`.

2.3.3 Public Key Details

2.3.3.1 Installation Image Signature Keys

The DEBIAN website makes available images of the operating system that can be installed onto and executed from removable media such as Compact Discs (CD), Digital Versatile Disc (DVD), and Universal Serial Bus (USB) storage devices. A set of GnuPG public key fingerprints have been listed on the `debian.org` website at <https://debian.org/CD/verify>. Table 2.3.1 summarizes the creation dates, long IDs, and availabilities of these keys. Full fingerprints and other information may be found in section 2.3.3.2.

2.3.1. Main website: <https://www.debian.org>.

2.3.2. See <https://tracker.debian.org/pkg/debian-keyring>

2.3.3. For a list of DEBIAN Project Leaders, see <https://www.debian.org/doc/manuals/project-history/leaders>.

Date	Long ID	Description	Available	Link
1999-01-30	7C3B 7970 88C7 C1F7	Debian CD signing key	2011–2015	^{2.3.4} ^{2.3.5}
2000-09-16	72FD C205 F6A3 2A8E	Santiago Garcia Mantinan	2011–2015	^{2.3.4} ^{2.3.6}
2004-06-20	F82E 5CC0 4B2B 2B9E	Daniel Baumann	2011–2015	^{2.3.4}
2009-05-21	39BE 2D72 5CEE 3195	Daniel Baumann	2011–2015	^{2.3.4}
2009-10-03	9880 21A9 64E6 EA7D	Debian CD signing key	2011–2021	^{2.3.4}
2011-01-05	DA87 E80D 6294 BE9B	Debian CD signing key	2011–2021	^{2.3.4} ^{2.3.5}
2011-03-09	6F95 B499 6CA7 B5A6	Debian Live Signing Key	2012–2015	^{2.3.7}
2013-05-06	510A D6B9 AD11 CF6A	Debian Live Signing Key	2013–2015	^{2.3.8}
2014-01-03	1239 00F2 A9B2 6DF5	Live Systems Project	2014–2015	^{2.3.9}
2014-04-15	4246 8F40 09EA 8AC3	Debian Testing CDs Automatic Signing Key	2014–2022	^{2.3.10}

Table 2.3.1. A list of keys used to sign DEBIAN installation images. Keys identified from INTERNET ARCHIVE snapshots of <https://debian.org/CD/verify>.

- 2.3.4. See <https://web.archive.org/web/20110413065857/http://www.debian.org/CD/verify>.
- 2.3.7. See <https://web.archive.org/web/20120815030316/http://www.debian.org:80/CD/verify>.
- 2.3.8. See <https://web.archive.org/web/20130813130619/http://www.debian.org/CD/verify>.
- 2.3.9. See <https://web.archive.org/web/20140410065231/http://www.debian.org/CD/verify>.
- 2.3.10. See <https://web.archive.org/web/20140528012106/https://www.debian.org/CD/verify>.
- 2.3.5. Public key available at <https://web.archive.org/web/20210928205206/https://www.einval.com/~steve/pgp/>.
- 2.3.6. Public key available at https://web.archive.org/web/20210928220426/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E..debian_manty.asc.

2.3.3.2 Verbose key details

Key 1999-01-30 (7C3B 7970 88C7 C1F7)

A 1024-bit DSA key that is the earliest dated key for signing Debian CDs mentioned at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE ^{2.3.11}. Mention of this key was removed from that page by the end of 2015. A copy of this key can be found at the personal website of STEVE MCINTYRE, a debian developer. ^{2.3.12}

```
pub dsa1024/0x7C3B797088C7C1F7 1999-01-30 [SCA] [revoked: 2017-01-11]
    Key fingerprint = AC65 6D79 E362 32CF 77BB B0E8 7C3B 7970 88C7 C1F7
uid [revoked] Steve McIntyre <313467b6>
uid [revoked] Steve McIntyre <8b5d9233>
uid [revoked] Steve McIntyre <032c14f6>
uid [revoked] Debian CD signing key <047be9f4>
```

Key 2000-09-16 (72FD C205 F6A3 2A8E)

A 1024-bit DSA key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE. Mention of this key was removed from that page by the end of 2015. A copy of this key was archived from the pgp.mit.edu keyserver. ^{2.3.13} This 1024-bit DSA key was deprecated in favor of a 4096-bit RSA key with fingerprint B868 8CA3 D876 D5A3 in a signed blog post at blog.manty.net. ^{2.3.14}

```
pub dsa1024/0x72FDC205F6A32A8E 2000-09-16 [SCA]
    Key fingerprint = 3FOA 12FC 0B55 A917 D791 82D3 72FD C205 F6A3 2A8E
uid [unknown] Santiago Garcia Mantinan (manty) <65783682>
uid [unknown] Santiago Garcia Mantinan (manty) <ad3a4b28>
uid [unknown] Santiago Garcia Mantinan (manty) <99df45ac>
sub elg1024/0x8F802C268D0EB704 2000-09-16 [E]
    Key fingerprint = 0481 1B16 A1BC E82B E985 26B7 8F80 2C26 8D0E B704
```

^{2.3.11.} See <https://web.archive.org/web/20110413065857/http://www.debian.org/CD/verify>.

^{2.3.12.} Key 7C3B 7970 88C7 C1F7 is available at <https://web.archive.org/web/20210928205229/https://www.einval.com/~steve/pgp/7C3B797088C7C1F7.asc>.

^{2.3.13.} Key 72FD C205 F6A3 2A8E is available at https://web.archive.org/web/20210928220426/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E..debian_manty.asc.

^{2.3.14.} Key transition statement available at <https://web.archive.org/web/20150614033612/http://blog.manty.net/2014/12/transitioning-from-0xf6a32a8e-to.html>. To verify, use `gpg --import` command on text copied from between the <listing> tags. A copy of this text is also archived at https://web.archive.org/web/2021092822521/https://reboil.com/res/2021/txt/20210928_72FDC205F6A32A8E_to_B8688CA3D876D5A3_pgp_transition_statement.txt.

Key 2004-06-20 (F82E 5CC0 4B2B 2B9E)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE. Mention of this key was removed from that page by the end of 2015.

```
pub  dsa1024/0xF82E5CC04B2B2B9E 2004-06-20 [SC] [expired: 2015-01-01]
    Key fingerprint = 709F 54E4 ECF3 1956 2332 6AE3 F82E 5CC0 4B2B 2B9E
uid  [ expired] Daniel Baumann <09d45987>
```

Key 2009-05-21 (39BE 2D72 5CEE 3195)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x39BE2D725CEE3195 2009-05-21 [SC]
    Key fingerprint = D2FB 633A DDC2 0485 CBCE 6D12 39BE 2D72 5CEE 3195
uid  [ unknown] Daniel Baumann <58c7ad3d>
uid  [ unknown] Daniel Baumann <1d8e385c>
uid  [ unknown] Daniel Baumann <612d81a0>
uid  [ unknown] Daniel Baumann <2260b338>
uid  [ unknown] Daniel Baumann <8f3d581a>
uid  [ unknown] Daniel Baumann <24ba8964>
uid  [ unknown] Daniel Baumann <09d45987>
uid  [ unknown] Daniel Baumann <5923ca47>
sub  rsa4096/0x2E86B0C2E7D77F65 2009-05-21 [E]
    Key fingerprint = 205A 272D 2838 238C 3058 C278 2E86 B0C2 E7D7 7F65
```

Key 2009-10-03 (9880 21A9 64E6 EA7D)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x988021A964E6EA7D 2009-10-03 [SC]
    Key fingerprint = 1046 ODAD 7616 5AD8 1FBC 0CE9 9880 21A9 64E6 EA7D
uid  [ unknown] Debian CD signing key <047be9f4>
```

Key 2011-01-05 (DA87 E80D 6294 BE9B)

A key listed as being a signing key for Debian CD images as of 2011 at <https://debian.org/CD/verify> according to the INTERNET ARCHIVE.

```
pub  rsa4096/0xDA87E80D6294BE9B 2011-01-05 [SC]
    Key fingerprint = DF9B 9C49 EAA9 2984 3258 9D76 DA87 E80D 6294 BE9B
uid  [ unknown] Debian CD signing key <047be9f4>
sub  rsa4096/0x642A5AC311CD9819 2011-01-05 [E]
    Key fingerprint = 47A8 EA16 451B F5C9 B691 5C64 642A 5AC3 11CD 9819
```

Key 2011-03-09 (6F95 B499 6CA7 B5A6)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2012, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x6F95B4996CA7B5A6 2011-03-09 [SC] [expired: 2021-02-01]
    Key fingerprint = 696F 95F0 88E4 D359 947F 7AEB 6F95 B499 6CA7 B5A6
uid  [ expired] Debian Live Signing Key <4719e7fe>
```

Key 2013-05-06 (510A D6B9 AD11 CF6A)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2013, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x510AD6B9AD11CF6A 2013-05-06 [SC]
    Key fingerprint = 1E4F 435C 4E9A 42B3 D9DF BE3A 510A D6B9 AD11 CF6A
uid  [ unknown] Debian Live Signing Key (2013) <4719e7fe>
sub  rsa4096/0x4E534D59B72E3E00 2013-05-06 [E]
    Key fingerprint = 407B 17AD 8CD1 B9D3 6891 262B 4E53 4D59 B72E 3E00
```

Key 2014-01-03 (1239 00F2 A9B2 6DF5)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2014, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x123900F2A9B26DF5 2014-01-03 [SC] [expires: 2025-01-01]
    Key fingerprint = 8A36 A2E8 91A5 C2A9 ODEB 7A8B 1239 00F2 A9B2 6DF5
uid  [ unknown] Live Systems Project <4719e7fe>
sub  rsa4096/0xA1A89023D0125917 2014-01-03 [E] [expires: 2025-01-01]
    Key fingerprint = A9E3 8E70 E798 7E03 285E D9C2 A1A8 9023 D012 5917
```

Key 2014-04-15 (4246 8F40 09EA 8AC3)

This key was mentioned at <https://debian.org/CD/verify> at the end of 2014, according to the INTERNET ARCHIVE.

```
pub  rsa4096/0x42468F4009EA8AC3 2014-04-15 [SC]
    Key fingerprint = F41D 3034 2F35 4669 5F65 C669 4246 8F40 09EA 8AC3
uid  [ unknown] Debian Testing CDs Automatic Signing Key <047be9f4>
sub  rsa4096/0x0C5470136BD05CFB 2014-04-15 [E]
    Key fingerprint = AEE9 9CA7 0C3E C4B3 1C75 2843 0C54 7013 6BD0 5CFB
```

2.4 ELECTRUM

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.4.1 Background

ELECTRUM^{2.4.1} is a BITCOIN wallet program first published by THOMAS VOEGTLIN (2BD5 824B 7F94 70E6) in 2013.^{2.4.2} The program permits creating and digitally signing and verifying BITCOIN transactions as well as messages. In contrast to BITCOIN CORE, the main ELECTRUM program is a “thin client” designed to require less CPU power and storage capacity in order to be able to run on mobile devices such as ANDROID phones. It therefore requires trusting an ELECTRUM server to provide it with current transaction data from the BITCOIN blockchain. One such server is ELECTRUMX^{2.4.3}, maintained by SOMBERNIGHT (E7B7 48CD AF5E 5ED9).

2.4.2 History

2011-12-14. Early I.A. mention of THOMAS VOEGTLIN's 2BD5 824B 7F94 70E6 key on <http://bitcoin-otc.com>.^{2.4.4}

2013-01-09. Earliest I.A. snapshot of <https://electrum.org/download.html> available.^{2.4.5}

2014-09-13. Earliest I.A. snapshot of <https://github.com/spesmilo/electrum> available.^{2.4.6}

2018-03-31. Creation date of SOMBERNIGHT's E7B7 48CD AF5E 5ED9 key.

2.4.3 Public Key Details

2.4.3.1 ELECTRUM client release signing key (v1.7–) (2BD5 824B 7F94 70E6)

OPENPGP key used by THOMAS VOEGTLIN (a.k.a. “ThomasV”) to sign ELECTRUM (a BITCOIN wallet program) releases since as early as version 1.7 in 2013^{2.4.7}. A copy of the key can be downloaded from the ELECTRUM website.^{2.4.8}

```
pub  rsa4096/0x2BD5824B7F9470E6 2011-06-15 [SC]
     Key fingerprint = 6694 D8DE 7BE8 EE56 31BE D950 2BD5 824B 7F94 70E6
uid          [ unknown] Thomas Voegtlin (https://electrum.org) <cab2cac8>
uid          [ unknown] ThomasV <45704e55>
uid          [ unknown] Thomas Voegtlin <45704e55>
sub  rsa4096/0x1A25C4602021CD84 2011-06-15 [E]
     Key fingerprint = 0A40 B328 1212 5B08 FCBF 90EC 1A25 C460 2021 CD84
```

2.4.3.2 ELECTRUMX server commit key (E7B7 48CD AF5E 5ED9)

OPENPGP key used by SOMBERNIGHT (a.k.a. “ghost43”^{2.4.9}) to sign ELECTRUMX (an ELECTRUM server) commits on GITHUB^{2.4.10} as of 2022-03-10. Note, this key is different from another key (CA9E EEC4 3DF9 11DC) used by SOMBERNIGHT to sign ELECTRUM releases.

```
pub  rsa4096/0xE7B748CD4AF5E5ED9 2018-03-31 [SC]
     Key fingerprint = 4AD6 4339 DFA0 5E20 B3F6 AD51 E7B7 48CD AF5E 5ED9
uid          [ unknown] SomberNight <dbf39566>
sub  rsa4096/0xB38EBEDF07698B05 2018-03-31 [E]
     Key fingerprint = 9145 6DB8 FDF2 16A9 3C37 FOA9 B38E BEDF 0769 8B05
sub  rsa4096/0xB33B5F232C6271E9 2018-03-31 [S]
     Key fingerprint = 6D7A 2116 DA90 9E00 AC21 108B B33B 5F23 2C62 71E9
```

2.4.1. Main website: <https://electrum.org>.

2.4.2. THOMAS VOEGTLIN's GITHUB page: <https://github.com/ecdsa>.

2.4.3. See <https://github.com/spesmilo/electrumx/>.

2.4.4. See <https://web.archive.org/web/20111214231353/http://bitcoin-otc.com/viewpgp.php?nick=ThomasV>.

2.4.5. See <https://web.archive.org/web/20130109155542/http://electrum.org/download.html>.

2.4.6. See <https://web.archive.org/web/20140913002252/https://github.com/spesmilo/electrum>.

2.4.7. See <https://web.archive.org/web/20130320184418/http://electrum.org/download.html>.

2.4.8. See <https://raw.githubusercontent.com/spesmilo/electrum/master/pubkeys/ThomasV.asc>.

2.4.9. SOMBERNIGHT's GITHUB page: <https://github.com/SomberNight>.

2.4.10. See <https://github.com/spesmilo/electrumx/commit/914938264e5621ea8980be6d3e69964e7f219d16>.

2.5 GITHUB

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.5.1 Background

GITHUB^{2.5.1} is a commercial GIT repository hosting service company founded in 2008. It was purchased by MICROSOFT in 2016.^[1]

2.5.2 History

2008. GITHUB founded in San Francisco.^[1]

2008-03-10. GITHUB parent company LOGICAL AWESOME, LLC registered in San Francisco by Chris Wanstrath.^{2.5.2}

2008-05-14. First snapshot of the <https://github.com> website on the INTERNET ARCHIVE.^{2.5.3}

2017-08-16. Creation date of the 4AEE 18F8 3AFD EB23 public key according to itself.

2017-11-14. Date of INTERNET ARCHIVE snapshot containing an early link to <https://github.com/web-flow.gpg> from a page on the help.github.com domain.^{2.5.4} Also the date of a post by GITHUB user jonathancross^{2.5.5} observing that the 4AEE 18F8 3AFD EB23 key appears to be a new feature^{2.5.6}:

Yeah, just experimented and saw the same thing. Strange new “feature” of GitHub it seems.

2018-06-04. First snapshot of the 4AEE 18F8 3AFD EB23 public key <https://github.com/web-flow.gpg> on the INTERNET ARCHIVE.^{2.5.7}

2021-05-25. Public key 4AEE 18F8 3AFD EB23 fingerprint explicitly published at GITHUB documentation website.^{2.5.8}

2.5.3 Public Key Details

2.5.3.1 Web-flow commit signing (4AEE 18F8 3AFD EB23)

As of 2021-07-19, when a user logs into github.com and creates a GIT commit through a web browser, GITHUB will automatically sign the commit against a GPG key^{2.5.9} with the fingerprint:

```
pub    rsa2048/0x4AEE18F83AFDEB23 2017-08-16 [SC]
       Key fingerprint = 5DE3 E050 9C47 EA3C F04A  42D3 4AEE 18F8 3AFD EB23
uid    [ unknown] GitHub (web-flow commit signing) <3ca48f8d>
```

This key is available for download at GITHUB's documentation website at <https://github.com/web-flow.gpg>.^{2.5.10} This particular link as well as the full key fingerprint was added to the GITHUB documentation repository in a commit dated 2021-05-25^{2.5.11}.

2.5.1. Main website: <https://github.com/>.

2.5.2. See <https://businesssearch.sos.ca.gov/Document/RetrievePDF?Id=200807010145-721605> and <https://businesssearch.sos.ca.gov/Document/RetrievePDF?Id=200807010145-2544282> from https://opencorporates.com/companies/us_ca/200807010145.

2.5.3. See <https://web.archive.org/web/20080514210148/http://github.com/>.

2.5.4. See <https://web.archive.org/web/20171114055613/https://help.github.com/articles/about-gpg/>.

2.5.5. Key fingerprint C0C0 7613 2FFA 7695. Key at <https://github.com/jonathancross.gpg>.

2.5.6. <https://github.com/keepassxreboot/keepassxc/issues/1183#issuecomment-344386172>.

2.5.7. <https://web.archive.org/web/20180604123146/https://github.com/web-flow.gpg>.

2.5.8. See <https://github.com/github/docs/commit/c4e1cb7a97704f0d90c0d6ed7e52d72b1e4946c1>.

2.5.9. See https://reboil.com/res/2021/txt/20210719_4AEE18F83AFDEB23.github.asc or <https://github.com/web-flow.gpg>.

2.5.10. See <https://docs.github.com/en/github/authenticating-to-github/managing-commit-signature-verification/about-commit-signature-verification>.

2.5.11. See <https://github.com/github/docs/commit/c4e1cb7a97704f0d90c0d6ed7e52d72b1e4946c1>.

2.6 RASPIBLITZ

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.6.1 Background

RASPIBLITZ^{2.6.1} is a software package designed to facilitate operation of a LIGHTNING NETWORK and BITCOIN node. The software is version controlled using GIT, with the main git repository available at GITHUB.^{2.6.2} As of 2021-07-18, the principal maintainer appears to be CHRISTIAN “ROOTZOL” ROTZOLL^{2.6.3}.

2.6.2 History

2019-09-03. The creation date of rootzol's 1C73 060C 7C17 6461 public key.

2019-09-05. ROOTZOL added their public key fingerprint 1C73 060C 7C17 6461 to the FAQ of the RASPIBLITZ GITHUB repository.^{2.6.4} They linked their keybase.io page as a source of the public key.

2020-10-31. The first snapshot of the raspiblitz.org website appeared on the Internet Archive.^{2.6.5}

2021-02-07. Andreas Antonopoulos posted a YouTube video identifying RASPIBLITZ as a popular Bitcoin full node software package.^{2.6.6}

2021-05-18. ROOTZOL added their public key fingerprint 1C73 060C 7C17 6461 to the README of the RASPIBLITZ GITHUB repository.

2.6.3 Public Key Details

2.6.3.1 CHRISTIAN “ROOTZOL” ROTZOLL (1C73 060C 7C17 6461)

ROOTZOL's PGP key^{2.6.7} may be downloaded from their Keybase page.^{2.6.8} Their fingerprint information is as follows:

```
pub  rsa4096/0x1C73060C7C176461 2019-09-03 [C]
    Key fingerprint = 92A7 46AE 33A3 C186 D014 BF5C 1C73 060C 7C17 6461
uid          [ unknown] Christian Rotzoll <bca61f43>
sub  rsa4096/0xAA9DD1B5CC5647DA 2019-09-03 [S] [expires: 2022-10-26]
    Key fingerprint = COEE 6145 31A4 16B4 CDB7 A2D7 AA9D D1B5 CC56 47DA
sub  rsa4096/0xD40D94E6C7C9B4D9 2019-09-03 [E] [expires: 2022-10-26]
    Key fingerprint = A7D4 DA62 95EC 365E 4CCF 05FC D40D 94E6 C7C9 B4D9
sub  rsa4096/0x1C29DC2F8D764F9A 2019-09-03 [A] [expires: 2022-10-26]
    Key fingerprint = AA80 506C FCAB 3405 84C4 9F0E 1C29 DC2F 8D76 4F9A
```

2.6.1. Main website: <https://raspiblitz.org/>.

2.6.2. See <https://github.com/rootzoll/raspiblitz>.

2.6.3. Their public key 0x1c73060c7c176461 is available at: <https://keybase.io/rootzoll>.

2.6.4. See <https://github.com/rootzoll/raspiblitz/commit/75ebdd8d571cccc427b5d023a25c6e2e9e8a2da2>.

2.6.5. See <https://web.archive.org/web/20201031223643/https://raspiblitz.org/>.

2.6.6. See <https://www.youtube.com/watch?v=AXUfwvhr3lg&t=26m27s>.

2.6.7. See https://reboil.com/res/2021/txt/20210719_0x1C73060C7C176461..raspiblitz_rootzol.asc

2.6.8. See https://keybase.io/rootzoll/pgp_keys.asc.

2.7 SATOSHI LABS

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.7.1 Background

SATOSHI LABS^{2.7.1} is a company that produces cryptocurrency hardware wallets called TREZOR^{2.7.2}. These devices enable a user to privately manage their private keys necessary to create transactions. Publishing transactions and viewing current balances typically requires software running on a computer connected to the internet. SATOSHI LABS uses an OpenPGP key to sign these software packages published on their website <https://trezor.io>.

SATOSHI LABS was founded in 2013 by MAREK “SLUSH” PALATINUS, PAVOL “STICK” RUSNÁK, and ALENA VRANOVA.^{2.7.3} It is based in Prague, Czech Republic.

As of 2022-01-03, the primary TREZOR program requiring verification is TREZOR SUITE.

2.7.2 History

2012-03-07. Creation date of PAVOL RUSNÁK’s personal PGP key (91F3 B339 B9A0 2A3D).

2014-07-18. First snapshot of <https://mytrezor.com> appears on the INTERNET ARCHIVE.^{2.7.4}

2017-01-11. mytrezor.com, buytrezor.com, and other domains migrated to <https://trezor.io>.^{2.7.5}

2017-01-28. The first snapshot of <https://trezor.io> appears on the INTERNET ARCHIVE.^{2.7.6}

2020-10-20. Creation date of the 2020 signing key (26A3 A566 62F0 E7E2).

2021-01-04. Creation date of the 2021 signing key (E21B 6950 A2EC B65C).

2021-07-14. TREZOR SUITE launched^{2.7.7} in order to replace an older web wallet implementation.^{2.7.8}

2.7.3 Public Key Details

2.7.3.1 PAVOL RUSNÁK (91F3 B339 B9A0 2A3D)

A key^{2.7.9} used by a developer named PAVOL “STICK” RUSNÁK.^{2.7.10} This key has been used to sign TREZOR software in the past^{2.7.11} such as TREZOR BRIDGE^{2.7.12} and other various GITHUB commits.

```
pub  rsa4096/0x91F3B339B9A02A3D 2012-03-07 [SC] [expires: 2024-06-16]
    Key fingerprint = 86E6 792F C27B FD47 8860 C110 91F3 B339 B9A0 2A3D
uid  [ unknown] Pavol Rusnák <343a72bf>
uid  [ unknown] Pavol Rusnák <707f7617>
uid  [ unknown] Pavol Rusnák <5144f42a>
uid  [ unknown] Pavol Rusnák <5aef3feb>
uid  [ unknown] [jpeg image of size 2449]
sub  rsa4096/0x22AF226D38DC1F4D 2012-03-07 [E] [expires: 2024-06-16]
    Key fingerprint = E177 6F65 0601 E596 9E7F 9E25 22AF 226D 38DC 1F4D
```

^{2.7.1.} Main website: <https://satoshilabs.com/>.

^{2.7.2.} Trezor website: <https://trezor.io/>.

^{2.7.3.} See <https://web.archive.org/web/20140627154535/http://satoshilabs.com/team/>.

^{2.7.4.} See <https://web.archive.org/web/20140718104157/https://mytrezor.com/>.

^{2.7.5.} See <https://web.archive.org/web/20201111170337/https://blog.trezor.io/new-trezor-io-55cf687c88d5?gi=3481ee5b4637>.

^{2.7.6.} See <https://web.archive.org/web/20170128023418/https://trezor.io/>.

^{2.7.7.} See <https://blog.trezor.io/trezor-suite-launches-8958c1d37d33>.

^{2.7.8.} See <https://github.com/trezor-graveyard>.

^{2.7.9.} Download key at <https://rusnak.io/public/pgp.txt>.

^{2.7.10.} Twitter: <https://twitter.com/pavolrusnak>.

^{2.7.11.} See <https://github.com/trezor/trezord-go/issues/211>.

^{2.7.12.} See <https://github.com/trezor/webwallet-data/tree/master/bridge>.

2.7.3.2 2020 Signing Key (26A3 A566 62F0 E7E2)

A key^{2.7.13} used to sign the software required by a PC to communicate with the TREZOR product line. Expired as of 2021-01-01.

```
pub  rsa4096/0x26A3A56662F0E7E2 2020-10-20 [SC] [expired: 2021-01-01]
     Key fingerprint = 5406 7D8B BF00 5541 81B5 AB8F 26A3 A566 62F0 E7E2
uid           [ expired] SatoshiLabs 2020 Signing Key
```

2.7.3.3 2021 Signing Key (E21B 6950 A2EC B65C)

A key^{2.7.14} used to sign the software required by a PC to communicate with the Trezor product line.

```
pub  rsa4096/0xE21B6950A2ECB65C 2021-01-04 [SC]
     Key fingerprint = EB48 3B26 B078 A4AA 1B6F 425E E21B 6950 A2EC B65C
uid           [ unknown] SatoshiLabs 2021 Signing Key
```

^{2.7.13.} Download key at <https://trezor.io/security/satoshilabs-2020-signing-key.asc>.

^{2.7.14.} Download key at <https://trezor.io/security/satoshilabs-2021-signing-key.asc>.

2.8 TAILS

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.8.1 Background

TAILS^{2.8.1} is a DEBIAN-based GNU/LINUX operating system designed to preserve user anonymity through default use of TOR for all network traffic.

TAILS is an acronym for THE (AMNESIC) INCOGNITO LIVE SYSTEM. The name reflects the fact that the project is the result of a 2010 merger between two TOR-related projects known as AMNESIA^{2.8.2} and INCOGNITO^{2.8.3}. In addition to differing sets of developers, the two projects were based on two different GNU/LINUX operating systems: AMNESIA used DEBIAN and INCOGNITO used GENTOO.

2.8.2 History

2009-06-20. Date of first commit in AMNESIA repository.^{2.8.4}

2010-04-07. INCOGNITO^{2.8.5} and AMNESIA merge.^{2.8.6} Renamed “THE (AMNESIC) INCOGNITO LIVE SYSTEM”.^{2.8.7}

2010-07-16. First I.A. snapshot of <http://amnesia.boum.org>.^{2.8.8}

2010-10-07. Creation date of the signing key **1202 821C BE2C D9C1**.

2011-03-17. First I.A. snapshot of <https://tails.boum.org>.^{2.8.9}

2015-01-18. Creation date of the signing key **DBB8 02B2 58AC D84F**.

2015-03-16. Signing key **1202 821C BE2C D9C1** officially retired and replaced by **DBB8 02B2 58AC D84F**.^{2.8.10}

2.8.3 Public Key Details

As of 2022, several public keys are associated with the TAILS project.^{2.8.11} This section describes only the current signing key (See 2.8.3.1), mailing list encryption key (See 2.8.3.3), and the 2010–2015 signing key (See 2.8.3.2).

2.8.3.1 Signing key (2015–) (**DBB8 02B2 58AC D84F**)

Key used by the TAILS developers to sign released .iso installation images since TAILS version *v1.3.1* which was released in 2015.^{2.8.12} The public key may be downloaded here^{2.8.13}.

^{2.8.1.} Main website: <https://tails.boum.org/>.

^{2.8.2.} See <https://web.archive.org/web/20100716170307/http://amnesia.boum.org/>.

^{2.8.3.} See phobos. “Incognito and The Tor Project sign a licensing agreement”. Website: blog.torproject.org. Date: 2008-06-27. Archive URL: <https://web.archive.org/web/20081120073057/http://blog.torproject.org/blog/incognito-and-tor-project-sign-licensing-agreement>. Archive date: 2008-11-20.

^{2.8.4.} See https://gitlab.tails.boum.org/tails/-/blob/345a927fbd6aa18a2bcd13331cbc2e22ef2e0639/config/chroot_local-includes/usr/share/doc/amnesia/Changelog.

^{2.8.5.} See <https://web.archive.org/web/20100108093152/http://anonymityanywhere.com/>.

^{2.8.6.} See: anonym. “Incognito + Amnesia = The (Amnesic) Incognito Live System”. Date: 2010-04-07. Archive date: 2010-07-28. Archive URL: <https://web.archive.org/web/20100728224716/http://www.anonymityanywhere.com:80/incognito>.

^{2.8.7.} See “new project name”. Website: amnesia.boum.org. Date: 2010-04-07. Archive date: 2010-08-17. Archive URL: https://web.archive.org/web/20100817180857/http://amnesia.boum.org/news/new_project_name/.

^{2.8.8.} See <https://web.archive.org/web/20100716170307/http://amnesia.boum.org/>.

^{2.8.9.} See <https://web.archive.org/web/20110317013911/https://tails.boum.org/>.

^{2.8.10.} See https://web.archive.org/web/20150316172733/https://tails.boum.org/news/signing_key_transition/index.en.html.

^{2.8.11.} See “OpenPGP keys”. Date accessed: 2022-03-12. https://tails.boum.org/doc/about/openpgp_keys/index.en.html.

^{2.8.12.} See “Tails 1.3.1 is out”. Website: tails.boum.org. Date: 2015-03-23. Archive URL: https://web.archive.org/web/20150402101752/https://tails.boum.org/news/version_1.3.1/index.en.html. Archive date: 2015-04-02.

^{2.8.13.} See <https://tails.boum.org/tails-signing.key>.

```

pub  rsa4096/0xDBB802B258ACD84F 2015-01-18 [C] [expires: 2023-01-07]
     Key fingerprint = A490 D0F4 D311 A415 3E2B B7CA DBB8 02B2 58AC D84F
uid  [ unknown] Tails developers (offline long-term identity key) <16f58847>
uid  [ unknown] Tails developers <16f58847>
sub  rsa4096/0xD21DAD38AF281C0B 2017-08-28 [S] [expires: 2023-01-07]
     Key fingerprint = 0546 9FB8 5EAD 6589 B43D 41D3 D21D AD38 AF28 1C0B
sub  ed25519/0x90B2B4BD7AED235F 2017-08-28 [S] [expires: 2023-01-07]
     Key fingerprint = CD4D 4351 AFA6 933F 574A 9AFB 90B2 B4BD 7AED 235F
sub  rsa4096/0x7BFBD2B902EE13D0 2021-10-14 [S] [expires: 2023-01-07]
     Key fingerprint = 753F 9013 77A3 09F2 731F A33F 7BFB D2B9 02EE 13D0

```

2.8.3.2 Signing key (2010–2015) (1202 821C BE2C D9C1)

Key used by the TAILS developers to sign released images starting with TAILS v0.6^{2.8.14} until and including v1.3. The public key may be downloaded here^{2.8.15}. This key was retired from use in 2015 and replaced with key DBB8 02B2 58AC D84F^{2.8.16}.

```

pub  rsa4096/0x1202821CBE2CD9C1 2010-10-07 [SC] [expired: 2015-04-30]
     Key fingerprint = 0D24 B36A A9A2 A651 7878 7645 1202 821C BE2C D9C1
uid  [ expired] Tails developers (signing key) <16f58847>

```

2.8.3.3 Mailing list key (2009–) (1D29 75ED F93E 735F)

Key recommended by the TAILS developers to be used to encrypt emails sent to their encrypted mailing list since at least 2011^{2.8.17}, possibly 2009^{2.8.18}, assuming the main repository timestamps are trustworthy. Until TAILS v0.5 and v0.6-rc3, released images were signed using this key.^{2.8.19} The public key may be downloaded here^{2.8.20}.

```

pub  rsa4096/0x1D2975EDF93E735F 2009-08-14 [SC] [expires: 2023-03-03]
     Key fingerprint = 09F6 BC8F EEC9 D8EE 005D BAA4 1D29 75ED F93E 735F
uid  [ unknown] Tails developers (Schleuder mailing-list) <16f58847>
uid  [ unknown] Tails list (schleuder list) <a6d8622b>
uid  [ unknown] Tails list (schleuder list) <87eb09d2>
sub  rsa4096/0xD843C2F5E89382EB 2009-08-14 [E] [expires: 2023-03-03]
     Key fingerprint = C394 8FE7 B604 C611 4E29 4DDF D843 C2F5 E893 82EB

```

2.8.14. See https://web.archive.org/web/20111205083704/https://tails.boum.org/doc/about/openpgp_keys/index.en.html.

2.8.15. See <https://web.archive.org/web/20141006010041/https://tails.boum.org/tails-signing.key>.

2.8.16. See “Transition to a new OpenPGP signing key”. Website: tails.boum.org. Date: 2015-03-16. Archive URL: https://web.archive.org/web/20150316172733/https://tails.boum.org/news/signing_key_transition/index.en.html. Archive date: 2015-03-16.

2.8.17. See https://web.archive.org/web/20110318070814/http://tails.boum.org/GnuPG_key/index.en.html.

2.8.18. See <https://gitlab.tails.boum.org/tails/tails/-/blob/195b39cbf409fa7a8763cc6a6c5f91386db6735b/debian/changelog>.

2.8.19. See https://web.archive.org/web/20111205083704/https://tails.boum.org/doc/about/openpgp_keys/index.en.html.

2.8.20. See <https://tails.boum.org/tails-email.key>.

2.9 TOR BROWSER

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.9.1 Background

TOR BROWSER^{2.9.1} is a browser software package that permits visiting websites with anonymity effected by onion routing. Although various^{2.9.2} PGP keys have been used to sign various releases and archives, the 4E2C 6E87 9329 8290 key has been used for the main TOR BROWSER installer since at least 2015.

2.9.2 History

2008-01-30. STEVEN J. MURDOCH announces development of TOR BROWSER.^{2.9.3}

2014-12-15. Creation date of the 4E2C 6E87 9329 8290 binary signing key.

2019-06-29. Copies of the main release signing key 4E2C 6E87 9329 8290 maintained by various key-servers suffered a certificate spamming attack.^{2.9.4} Other high-profile PGP keys were also affected at this time.^{2.9.5}

2.9.3 Public Key Details

2.9.3.1 Release Signing Key (2015–) (4E2C 6E87 9329 8290)

Public key used for signing TOR BROWSER releases since at least 2015-03-15^{2.9.6} until 2022-03-06^{2.9.7}.

```
pub  rsa4096/0x4E2C6E8793298290 2014-12-15 [C] [expires: 2025-07-21]
    Key fingerprint = EF6E 286D DA85 EA2A 4BA7 DE68 4E2C 6E87 9329 8290
uid  [ unknown] Tor Browser Developers (signing key) <85e84cd9>
sub  rsa4096/0xE53D989A9E2D47BF 2021-09-17 [S] [expires: 2023-09-17]
    Key fingerprint = 6131 88FC 5BE2 176E 3ED5 4901 E53D 989A 9E2D 47BF
```

2.9.1. Main website: <https://www.torproject.org>.

2.9.2. See <https://web.archive.org/web/20210713130216/https://2019.www.torproject.org/docs/signing-keys.html.en>.

2.9.3. See <https://lists.torproject.org/pipermail/tor-talk/2008-January/007837.html>.

2.9.4. See <https://nvd.nist.gov/vuln/detail/CVE-2019-13050>.

2.9.5. See <https://gist.github.com/rjhansen/67ab921ffb4084c865b3618d6955275f#gistcomment-2959168>.

2.9.6. See <https://web.archive.org/web/20150315013830/https://www.torproject.org/docs/verifying-signatures.html.en>.

2.9.7. See <https://web.archive.org/web/20220221121737/https://support.torproject.org/tbb/how-to-verify-signature/>.

2.10 VERACRYPT

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.10.1 Background

VERACRYPT^{2.10.1} is an encryption software package compatible with WINDOWS, MACOS, and GNU/LINUX operating systems. The program is primarily maintained by MOUNIR IDRASSI.

VERACRYPT is a fork of TRUECRYPT made in 2013.

2.10.2 History

2013-06-29. First I.A. snapshot of <http://veracrypt.codeplex.com>, VERACRYPT's first public repository address.

2014-07-15. Early mention of full **EB55 9C7C 54DD D393** fingerprint on www.idrix.fr website.^{2.10.2}

2014-05-28. TRUECRYPT development halt announcement posted on SOURCEFORGE repository.^{2.10.3}

2014-06-27. Creation date of signing key **EB55 9C7C 54DD D393**.

2016-10-17. VERACRYPT *v1.18* audited by QUARKSLAB and *v1.19* released to fix most reported vulnerabilities.^{2.10.4}

2017-05-25. First I.A. snapshot of <https://veracrypt.fr> ^{2.10.5}, the new website made in response to MICROSOFT shutting down codeplex.com in 2017^{2.10.6}.

2018-09-11. Creation date of signing key **821A CD02 680D 16DE**.

2018-09-12. Signing key **EB55 9C7C 54DD D393** retired and replaced by key **821A CD02 680D 16DE** via a transition statement signed by both keys.^{2.10.7}

2.10.3 Public Key Details

2.10.3.1 Signing key (2018–) (**821A CD02 680D 16DE**)

Key used to sign VERACRYPT releases since version *v1.23* in 2018. A copy of this key can be downloaded here^{2.10.8}.

```
pub  rsa4096/0x821ACD02680D16DE 2018-09-11 [SC]
     Key fingerprint = 5069 A233 D55A OEEB 174A 5FC3 821A CD02 680D 16DE
uid          [ unknown] VeraCrypt Team (2018 - Supersedes Key ID=0x54DDD393) <8042d942>
sub  rsa4096/0x200B5A9D26878A32 2018-09-11 [E]
     Key fingerprint = BB33 5DCA 0D75 325C 6126 BAB6 200B 5A9D 2687 8A32
sub  rsa4096/0x0F5AACD65483D029 2018-09-11 [A]
     Key fingerprint = 6022 69E6 D482 C250 0D1C 2D87 0F5A ACD6 5483 D029
```

^{2.10.1.} Main website: <https://veracrypt.fr>.

^{2.10.2.} See <https://web.archive.org/web/20140715152305/http://www.idrix.fr:80/Root/content/category/7/32/60>.

^{2.10.3.} Goodin, Dan. "Truecrypt is not secure,' official SourceForge page abruptly warns". Date: 2014-05-28. URL: <https://arstechnica.com/information-technology/2014/05/truecrypt-is-not-secure-official-sourceforge-page-abruptly-warns/>. Access date: 2022-03-12. Archive URL: <https://web.archive.org/web/20140529084822/http://arstechnica.com/security/2014/05/truecrypt-is-not-secure-official-sourceforge-page-abruptly-warns/>. Archive date: 2014-05-29.

^{2.10.4.} ostifadmin. "The Veracrypt Audit Results". Website: ostif.org. Date: 2016-10-17. URL: <https://ostif.org/the-veracrypt-audit-results/>. Archive URL: <https://web.archive.org/web/20161017182455/https://ostif.org/the-veracrypt-audit-results/>. Archive date: 2016-10-17.

^{2.10.5.} See <https://web.archive.org/web/20170525235647/https://www.veracrypt.fr/en/Home.html>.

^{2.10.6.} Harry, Brian. "Shutting down CodePlex". Website: devblogs.microsoft.com. Date: 2017-03-31. Access date: 2022-03-12. <https://devblogs.microsoft.com/bharry/shutting-down-codeplex/>.

^{2.10.7.} See <https://web.archive.org/web/20181223051800/https://veracrypt.fr/pgp-key-transition-2018-09-12.txt>.

^{2.10.8.} See https://web.archive.org/web/20220211073947/https://www.idrix.fr/VeraCrypt/VeraCrypt_PGP_public_key.asc.

2.10.3.2 Signing key (2014–2018) (EB55 9C7C 54DD D393)

Key used to sign VERACRYPT releases prior to version *v1.23* in 2018. This key was used to sign the version of VERACRYPT audited by QUARKSLAB in 2016 (*v1.18*). A 2014 copy of this public key is available here^{2.10.9}.

```
pub  rsa4096/0xEB559C7C54DD393 2014-06-27 [SCE]
     Key fingerprint = 993B 7D7E 8E41 3809 828F 0F29 EB55 9C7C 54DD D393
uid           [ unknown] VeraCrypt Team <8042d942>
```

2.10.9. See https://web.archive.org/web/20200307044514/https://www.idrix.fr/VeraCrypt/VeraCrypt_PGP_public_key_2014.asc.

2.11 YOUTUBE-DL

Last updated 2022-03-12 by STEVEN BALTAKATEI SANDOVAL.

2.11.1 Background

YOUTUBE-DL^{2.11.1} is a PYTHON2-based^{2.11.2} program that can be used to download audio-visual media files from sites including, but not limited to, YOUTUBE. The software gained notoreity in 2020 when GITHUB took down the project page upon receiving a DMCA takedown notice issued by the RIAA.^{2.11.3}

As of 2021, the project maintainer was SERGEY M. (2C39 3E0F 18A9 236D).

Since 2021-12-25, the core developer is REMITA AMINE^{2.11.4} (?).

2.11.2 History

2008-07-21. First commit in the main project GIT repository published by RICARDO GARCIA.^{2.11.5}

2013-08-01. First image of the homepage <https://yt-dl.org> appears on the INTERNET ARCHIVE.

2020-10-23. GITHUB project page taken down due to DCMA takedown notice^{2.11.6} issued by the RIAA.^{2.11.7}

2020-11-16. GITHUB page for YOUTUBE-DL reinstated.^{2.11.8}

2021-12-25. The only active developer is REMITA AMINE (?).^{2.11.9}

2022-01-29. The project announced^{2.11.10} that it is seeking a new maintainer, that YOUTUBE-DL would continue to support PYTHON2, and that the fork YT-DLP created by PUKKANDAN (7EEE 9E1E 817D 0A39) would support PYTHON3.

2.11.3 Public Key Details

2.11.3.1 Binary signing key. SERGEY M. (2C39 3E0F 18A9 236D)

The binary signing key used to sign releases as of 2021. Owned by Sergey M.

```
pub  rsa4096/0x2C393E0F18A9236D 2016-04-09 [SC]
    Key fingerprint = ED7F 5BF4 6B3B BED8 1C87 368E 2C39 3E0F 18A9 236D
uid  [ unknown] Sergey M. <7345ddad>
sub  rsa4096/0xC3A4FE63297B1CE1 2016-04-09 [E]
    Key fingerprint = 9AA4 FB39 3AF2 73FF 56F9 8251 C3A4 FE63 297B 1CE1
```

2.11.3.2 Binary signing key. PHILIPP HAGEMEISTER (F5EA B582 FAFB 085C)

A binary signing key used by Philipp Hagemeister to sign releases sometime before 2021.^{2.11.11}

```
pub  dsa1024/0xF5EAB582FAFB085C 2006-10-23 [SCA] [expired: 2015-12-31]
    Key fingerprint = 0600 E1DB 6FB5 3A5D 95D8 FC0D F5EA B582 FAFB 085C
uid  [ expired] Philipp Hagemeister <6a728fcb>
uid  [ expired] Philipp Hagemeister <9482dbb6>
```

^{2.11.1.} Main website: <https://yt-dl.org>.

^{2.11.2.} See <https://developers.slashdot.org/story/22/01/30/003205/youtube-dl-forks-to-continue-supporting-older-versions-of-python>.

^{2.11.3.} See <https://www.zdnet.com/article/riaa-blitz-takes-down-18-github-projects-used-for-downloading-youtube-videos/>.

^{2.11.4.} See <https://github.com/remitamine>. Created YT-DLP commit 80d41482 signed by E0DE 62EF 9A9B FAB2.

^{2.11.5.} See <https://github.com/yt-dl-org/youtube-dl/commit/4fa74b5252a23c2890dde52b8ee5811b5bb2987>.

^{2.11.6.} See <https://github.com/github/dmca/blob/master/2020/10/2020-10-23-RIAA.md>.

^{2.11.7.} See <https://web.archive.org/web/20201023194520/https://github.com/yt-dl-org/youtube-dl>.

^{2.11.8.} See <https://github.blog/2020-11-16-standing-up-for-developers-youtube-dl-is-back/>.

^{2.11.9.} See <https://web.archive.org/web/20211225064545/https://yt-dl-org.github.io/youtube-dl/about.html>.

^{2.11.10.} See <https://github.com/yt-dl-org/youtube-dl/issues/30568>.

^{2.11.11.} See <https://phihag.de/keys/A4826A18.asc>.

2.11.3.3 Binary signing key. PHILIPP HAGEMEISTER (DB4B 54CB A482 6A18)

A binary signing key used by Philipp Hagemeister to sign releases sometime before 2021.

```
pub  rsa4096/0xDB4B54CBA4826A18 2013-01-11 [SC] [expires: 2033-01-06]
     Key fingerprint = 7D33 D762 FD6C 3513 0481 347F DB4B 54CB A482 6A18
uid      [ unknown] Philipp Hagemeister <9482dbb6>
uid      [ unknown] Philipp Hagemeister <3ec335f6>
uid      [ unknown] Philipp Hagemeister <7787a9ff>
sub  rsa4096/0x862A257D825E38B8 2013-01-11 [E] [expires: 2033-01-06]
     Key fingerprint = 61F8 AC9E 8A81 6A5F 9BD8 B922 862A 257D 825E 38B8
```

2.11.3.4 Binary signing key. FILIPPO VALSORDA (EBF0 1804 BCF0 5F6B)

A binary signing key used by Filippo Valsorda to sign releases sometime before 2021.

```
pub  rsa4096/0xEBF01804BCF05F6B 2012-08-30 [SCEA]
     Key fingerprint = 428D F5D6 3EF0 7494 BB45 5AC0 EBF0 1804 BCF0 5F6B
uid      [ unknown] Filippo Valsorda <7970bea1>
uid      [ unknown] Filippo Valsorda <651b1dcc>
uid      [ unknown] Filippo Valsorda <1b03dbe9>
```


Appendix A

How Public Key Cryptography Works

This appendix describes in more detail how public key cryptography works.

Appendix B

How to use GnuPG

This appendix describes in more detail how to use GnuPG. Examples assume use of GnuPG version 2.2.12.

B.1 Definitions

Long ID. A 16-digit hexadecimal number used to identify a public key, e.g. `A0A2 95AB DC34 69C9`. Its hexadecimal nature may be emphasized by prepending the string with the “0x” prefix and omitting spaces, e.g. `0xA0A295ABDC3469C9`.^{B.1.1} GnuPG is not particular about whether letters in the Long ID are upper or lowercase, so `0xa0a295abdc3469c9` is also acceptable.

Short ID. An 8-digit hexadecimal number similar to a Long ID. Use of Short IDs is not recommended because, as of 2021, generating multiple public keys with matching Short IDs requires a negligible amount of computing power.^{B.1.2}

Remark B.1.1. Example code is sometimes given in the form of a BASH script. Such scripts usually have a first line like `#!/usr/bin/env bash` that tell your interpreter to execute the lines that follow as BASH commands. This is useful from a typography standpoint because often the length of GnuPG commands can exceed the recommended character limit for human readability.^{B.1.3} This document will attempt to limit line widths in code examples to approximately 80 characters.

B.2 Useful Commands

B.2.1 Obtaining keys

B.2.1.1 Import a public key

The `$ gpg --import key.asc` command may be used to import a file named “key.asc”. If the `$ gpg --import` command by itself is run and a clipboard program is available (e.g. copy/paste), then pasting the text of a public key into the shell followed by pressing `ctrl-d` (i.e. providing an “end of transmission” character^{B.2.1}) will tell `gpg` to process the pasted text.

B.2.1.2 Download from a keyserver

The `$ gpg --receive-keys` command can be used as shown in the example below to download a public key (e.g. `4246 8F40 09EA 8AC3`) from a keyserver (e.g. `keyserver.ubuntu.com`).

```
$ gpg --receive-keys --keyserver keyserver.ubuntu.com 42468f4009ea8ac3
gpg: key 0x42468F4009EA8AC3: public key "Debian Testing CDs Automatic... <047be9f4>" imported
gpg: Total number processed: 1
gpg: imported: 1
```

B.1.1. See <https://stackoverflow.com/questions/2670639/why-are-hexadecimal-numbers-prefixed-with-0x>.

B.1.2. See <https://security.stackexchange.com/questions/84280/>.

B.1.3. EMACS, for example, defaults to wrapping columns of text to 70. See <https://emacs.stackexchange.com/questions/36118/>.

B.2.1. See <https://unix.stackexchange.com/a/110248>.

As of 2022-01-14, few keyserver provide full public keys due to an unsolved certificate spam problem.^{B.2.2}

- keyserver.ubuntu.com - Provides full keys.
- keyring.debian.org - Provides full keys of DEBIAN developer and maintainers.
- keys.openpgp.org - Provides keys without user IDs unless key owner authenticates themselves via the user ID email address.

B.2.2 Analyzing keys

B.2.2.1 View public key fingerprint

- Show fingerprints of the primary key and subkeys. The example below shows the primary fingerprint in **red**, the Long ID colored in **brown**, user IDs in **blue**^{B.2.3}, and fingerprints of subkeys **dark green**.

```
$ gpg --fingerprint 0xa0a295abdc3469c9
pub  rsa4096/0xA0A295ABDC3469C9 2017-10-11 [C] [expires: 2022-07-08]
    Key fingerprint = 3457 A265 922A 1F38 39DB 0264 A0A2 95AB DC34 69C9
uid                               [ultimate] Steven Sandoval <baltakatei@gmail.com>
uid                               [ultimate] Steven Sandoval <baltakatei@alumni.stanford.edu>
sub  rsa4096/0x6DD7D496916A1253 2018-05-16 [E] [expires: 2022-07-07]
    Key fingerprint = 5E55 5FC6 1C85 871E 813B 5BCF 6DD7 D496 916A 1253
sub  rsa4096/0x57DA57D9517E6F86 2018-05-16 [S] [expires: 2022-07-07]
    Key fingerprint = 38F9 6437 C83A C88E 28B7 A952 57DA 57D9 517E 6F86
sub  rsa4096/0x5F9D26B9A598A2D3 2018-05-16 [A] [expires: 2022-07-07]
    Key fingerprint = EDCA 7EE7 D09E 7F2E 1DF6 A229 5F9D 26B9 A598 A2D3
```

B.2.3 Sending keys

B.2.3.1 Export public key

- Export public key according to last 16 characters of public key fingerprint (i.e. “long ID”, e.g. **A0A2 95AB DC34 69C9**).

```
$ gpg --export --output /tmp/key 0xa0a295abdc3469c9.
```

- Export the smallest key possible. Useful to strip key of signatures except for self-signatures. This creates an ASCII-armored^{B.2.4} text file named **pubkey.asc** in the **/tmp** directory.

```
#!/usr/bin/env bash
gpg --export --export-options export-minimal \
  --armor \
  --output /tmp/pubkey.asc \
  0xa0a295abdc3469c9
```

B.2.4 Creating keys

B.2.4.1 Using default settings

Running `$ gpg --gen-key` will guide the user to creating a key with default settings.

B.2.4.2 With subkeys

The `$ gpg --expert --full-gen-key` command in combination with some modifications to the configuration file `~/.gnupg/gpg.conf` may be used to create an OpenPGP key with subkeys. Subkeys are useful since their private components can be loaded onto a smartcard while keeping the primary key offline, available to create new subkeys. This may be desirable if a primary key is intended to be used over a long time period and the risk of losing an online defaultly configured key is unacceptable. Please see the article by THIERRY THURON titled “OpenPGP - The Almost Perfect Key Pair” for a useful procedure.^{B.2.5}

^{B.2.2.} Hansen, Robert J.. “SKS Keyserver Network Under Attack”. 2019-06-29. <https://gist.github.com/rjhansen/67ab921ffb4084c865b3618d6955275f>.

^{B.2.3.} In this publication, I may obfuscate email addresses via a `b2sum -132` hash if I cannot confirm the key owner is okay with their email address being posted so plainly.

^{B.2.4.} See <https://crypto.stackexchange.com/questions/91984/why-use-ascii-armor-for-file-encryption>.

^{B.2.5.} Thuron, Thierry. “OpenPGP - The Almost Perfect Key Pair”. 2017-10-13. Eleven Labs Blog. <https://blog.eleven-labs.com/en/openpgp-almost-perfect-key-pair-part-1/>.

Bibliography

[1] Steve Lohr . Microsoft Buys GitHub for \$7.5 Billion, Moving to Grow in Coding's New Era. *New York Times*, 2018.

Index

DSA, algorithm		
weakness	14	
Keys		
Organizations		
Cryptomator		
0x509C9D6334C80F11	15	
0x615D449FE6E6A235	16	
GitHub		
0x4AEE18F83AFDEB23	22	
Satoshi Labs		
Signing		
0x26A3A56662F0E7E2 (2020)	25	
0xE21B6950A2ECB65C (2021)	25	
Tails		
Mailing list		
0x1D2975EDF93E735F (2009–)	27	
Signing		
0x1202821CBE2CD9C1 (2010–2015)	27	
0xDBB802B258ACD84F (2015–)	26	
Tor Browser		
Signing		
0x4E2C6E8793298290 (2015–)	28	
Organizations		
Veracrypt		
0x821ACD02680D16DE (2018–)	29	
0xEB559C7C54DDD393 (2014–2018)	30	
People		
Andresen, Gavin		
0x29D9EE6B1FC730C1	13	
Hagemann, Tobias		
0x69CEFAAD519598989	15	
Hagemeister, Philipp		
0xDB4B54CBA4826A18	32	
0xF5EAB582FAB085C	31	
D., Sergey		
0x2C393E0F18A9236D	31	
Nakamoto, Satoshi		
0x18C09E865EC948A1	14	
Rotzoll, Christian “rootzol”		
0x1C73060C7C176461	23	
Rusnák, Pavol “Stick”		
0x91F3B339B9A02A3D	24	
Schrenk, Armin		
0x748E55D51F5B3FBC	15	
SomberNight		
0xE7B748CDAF5E5ED9	21	
Stenzel, Sebastian		
0x667B86EA8240A09	15	
Valsorda, Filippo		
0xEBF01804BCF05F6B	32	
van der Laan, Wladimir J.		
0x74810B012346C9A6 (personal; 2011–)	13	
0x90C8019E36C2E964 (Bitcoin Core; 2015–2022)	13	
Voegtlin, Thomas		
0x2BD5824B7F9470E6	21	
Logical Awesome, LLC	22	
Microsoft	22	
Organization		
QuarksLab	29, 30	
Organizations		
Bitcoin Foundation	14	
People		
Amine, Remita	31	
Andresen, Gavin	12	
Antonopoulos, Andreas	23	
Baumann, Daniel	17	
Cross, Jonathan	22	
Garcia, Ricardo	31	
Hagemeister, Philipp	31, 32	
Idrassi, Mounir	29	
M., Sergey	31	
Mantinan, Santiago Garcia	17	
McIntyre, Steve	18	
Murdoch, Steven J.	28	
Murdock, Ian Ashley	17	
Nakamoto, Satoshi	12	
Palatinus, Marek “Slush”	24	
Rotzoll, Christian “rootzol”	23	
Rusnák, Pavol “Stick”	24	
Slush (Satoshi Labs developer)	24	
SomberNight	21	
Stick (Satoshi Labs developer)	24	
Todd, Peter	12	
Valsorda, Filippo	32	
van der Laan, Wladimir J.	12	
Voegtlin, Thomas	21	
Vranova, Alena	24	
Wanstrath, Chris	22	
Software		
Amnesia	26	
Android	21	
Bitcoin	12, 23	
Bitcoin Core	12–14, 21	
Cryptomator	15–16	
Debian	17–20, 26	
Dropbox	15	
Electrum	21–21	
ElectrumX	21	
Gentoo	26	
GitHub	22–22	
Incognito	26	
Lightning Network	23	
RaspiBlitz	23–23	
Satoshi Labs	24–25	
Tails	26–27	
Tor	26	
Tor Browser	28–28, 28	
Trezor	24	
Veracrypt	29–30	
Youtube-dl	31–32	